

# A423S1CWZQ

# A423S1CWZQ Information

Heisener.com	Part Number Manufacturer Category Description Package	A423S1CWZQ Electroswitch Switches Toggle Switches SWITCH TOGGLE 4PDT 6A 125V - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## A423S1CWZQ Specifications

Manufacturer Part Number A423S1CWZQ   Manufacturer Electroswitch   Category Switches   Toggle Switches Toggle Switches   Package -   Series A   Circuit 4PDT   Switch Function On-On   Current Rating 6A (AC/DC)   Voltage Rating - AC 125V   Voltage Rating - DC 28V   Actuator Length 10.41mm   Illumination Non-Illuminated   Illumination Type, Color -   Illumination Type, Color -   Termination Style Solder Lug   Panel Cutout Dimensions -   Bushing Thread 1/440   Ingress Protection Splash Proof   Features Epoxy Sealed Terminals		
CategorySwitchesToggle SwitchesPackage-SeriesACircuit4PDTSwitch FunctionOn-OnCurrent Rating6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DCSatdard RoundActuator TypeStandard RoundIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Young TypeSolder LugMounting TypeSolder LugInden StyleSolder LugPanel Cutout Dimensions-Ingress ProtectionSpasProtectionFeaturesSpasPaced Terminales	Manufacturer Part Number	A423S1CWZQ
Togle SwitchesPackage-SeriesACircuit4PDTSwitch FunctionOn-OnCurrent Rating6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeStandard RoundIlluminationNon-IlluminatedIllumination Type, Color-Illumination TypeSolder LugMounting TypeSolder LugPanel Mounting TypeSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress ProtectionSpash ProofFeaturesEpoxy Sealed Terminals	Manufacturer	Electroswitch
Package-SeriesACircuit4PDTSwitch FunctionOn-OnCurrent Rating6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DCStandard RoundActuator TypeStandard RoundActuator Length10.41mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Parent Actuator LengthStoler LugIllumination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress ProtectionSplash ProofFeaturesEpoxy Sealed Terminals	Category	Switches
SeriesACircuit4PDTSwitch FunctionOn-OnCurrent Rating6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length10.41mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/440Ingress ProtectionSpash ProofFeaturesEpoxy Sealed Terminals		Toggle Switches
Circuit4PDTSwitch FunctionOn-OnCurrent RatingOn-OnCurrent Rating - AC6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DCSandard RoundActuator TypeStandard RoundActuator Length10.41mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/440Ingress ProtectionSpash ProofFeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionOn-OnCurrent Rating6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length10.41mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugPanel Cutout Dimensions-Illumination Style-Bushing Thread1/4-40Ingress ProtectionSpas ProtectionFeaturesEpoxy Sealed Terminals	Series	А
Current Rating6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length10.41mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress ProtectionSpash ProofFeaturesEpoxy Sealed Terminals	Circuit	4PDT
Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeStandar RoundActuator Length10.41mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountPanel Cutout Dimensions-Bushing Thread1/440Ingress ProtectionSplash ProofFeaturesEpoxy Sealed Terminals	Switch Function	On-On
Voltage Rating - DC28VActuator TypeStandard RoundActuator Length10.41mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress ProtectionSplash ProofFeaturesEpoxy Sealed Terminals	Current Rating	6A (AC/DC)
Actuator TypeStandard RoundActuator Length10.41mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress ProtectionSplash ProofFeaturesEpoxy Sealed Terminals	Voltage Rating - AC	125V
Actuator Length10.41mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress ProtectionSplash ProofFeaturesEpoxy Sealed Terminals	Voltage Rating - DC	28V
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress ProtectionSplash ProofFeaturesEpoxy Sealed Terminals	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress ProtectionSplash ProofFeaturesEpoxy Sealed Terminations	Actuator Length	10.41mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress ProtectionSplash ProofFeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress ProtectionSplash ProofFeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress ProtectionSplash ProofFeaturesEpoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions-Bushing Thread1/4-40Ingress ProtectionSplash ProofFeaturesEpoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread1/4-40Ingress ProtectionSplash ProofFeaturesEpoxy Sealed Terminals	Termination Style	Solder Lug
Ingress ProtectionSplash ProofFeaturesEpoxy Sealed Terminals	Panel Cutout Dimensions	-
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	Splash Proof
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

#### A423S1CWZQ Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### A423S1CWZQ Payment Methods





If you have any question about A423S1CWZQ, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com