



A433P32YZQ Information

Heisener.com

For Reference Only

Category

Part Number A433P32YZQ Manufacturer Electroswitch Switches

Toggle Switches

Description SWITCH TOGGLE DP3T 6A 125V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









A433P32YZQ Specifications

Manufacturer Part Number A433P32YZQ Manufacturer Electroswitch Category Switches Package - Series A Circuit DP3T Switch Function On-On-Mom Current Rating 6A (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 28V Actuator Type Flatted Actuator Length 11.38mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw		
CategorySwitchesPackage-SeriesACircuitDP3TSwitch FunctionOn-On-MomCurrent Rating6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeFlattedActuator Length11.38mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Manufacturer Part Number	A433P32YZQ
Package - Greis A A - Circuit DP3T Switch Function On-On-Mom On-On-On-On-On-On-On-On-On-On-On-On-On-O	Manufacturer	Electroswitch
Package - A Series A A Circuit DP3T Switch Function On-On-Mom Current Rating 6A (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 28V Actuator Type Flatted Actuator Length 11.38mm Illumination Type, Color 11luminated 11lumination Type, Color 11lumination Voltage (Nominal) - Illumination Voltage (Nominal) - Solder Lug Panel Cutout Dimensions - Solder Lug Panel Cutout Dimensions - Subming Thread 1/4-40 Ingress Protection - Jumper needed to achieve triple throw	Category	Switches
SeriesACircuitDP3TSwitch FunctionOn-On-MomCurrent Rating6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeFlattedActuator Length11.38mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw		Toggle Switches
CircuitDP3TSwitch FunctionOn-On-MomCurrent Rating6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeFlattedActuator Length11.38mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Package	-
Switch Function Current Rating 6A (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 28V Actuator Type Flatted Actuator Length 11.38mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection Features On-On-Mom 6A (AC/DC)	Series	A
Current Rating 6A (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 28V Actuator Type Flatted Actuator Length 11.38mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Circuit	DP3T
Voltage Rating - AC Voltage Rating - DC 28V Actuator Type Flatted Actuator Length 11.38mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection Features 125V 28V Patted Patted Non-Illumination Non-Illuminated 11.38mm Non-Illuminated 11.38mm Non-Illuminated 11.38mm Non-Illuminated Solder Lug Panel Mount 1- 1- 1- 1- 1- 1- 1- 1- 1- 1-	Switch Function	On-On-Mom
Voltage Rating - DC Actuator Type Flatted Actuator Length 11.38mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions - Bushing Thread Ingress Protection Features Jumper needed to achieve triple throw	Current Rating	6A (AC/DC)
Actuator Type Actuator Length 11.38mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Subshing Thread Ingress Protection Features Features Flatted Non-Illuminated Flatted Non-Illuminated Solder Lug Panel Mount Tomper Mount Solder Lug Flatted Ingress Protection Jumper needed to achieve triple throw	Voltage Rating - AC	125V
Actuator Length 11.38mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Voltage Rating - DC	28V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Actuator Type	Flatted
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection Features Jumper needed to achieve triple throw	Actuator Length	11.38mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Illumination	Non-Illuminated
Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Illumination Type, Color	-
Termination Style Solder Lug Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Bushing Thread Ingress Protection Features Jumper needed to achieve triple throw	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Termination Style	Solder Lug
Ingress Protection - Features Jumper needed to achieve triple throw	Panel Cutout Dimensions	-
Features Jumper needed to achieve triple throw	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Jumper needed to achieve triple throw
		Report errors?

A433P32YZQ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

A433P32YZQ Payment Methods



















A433P32YZQ Shipping Methods













If you have any question about A433P32YZQ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com