

# A562K20X7RL5UAA

### A562K20X7RL5UAA Information

Part Number A562K20X7RL5UAA

Manufacturer Vishay BC Components

**Category** Capacitors

Ceramic Capacitors

**Description** CAP CER 5600PF 500V X7R AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

sdept@heisener.com

Request a Quote



## **Certified Quality**

www.hellener.com

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## A562K20X7RL5UAA Specifications

Manufacturer Part Number         A562K20X7RL5UAA           Manufacturer         Vishay BC Components           Category         Capacitors           Package         Axial           Series         A           Capacitance         5600pF           Tolerance         ±10%           Voltage - Rated         500V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.118" Dia x 0.197" L (3.00mm x 5.00mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -		
Category         Capacitors           Package         Axial           Series         A           Capacitance         5600pF           Tolerance         ±10%           Voltage - Rated         500V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.118" Dia x 0.197" L (3.00mm x 5.00mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	A562K20X7RL5UAA
Package         Axial           Series         A           Capacitance         5600pF           Tolerance         ±10%           Voltage - Rated         500V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.118" Dia x 0.197" L (3.00mm x 5.00mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -	Manufacturer	Vishay BC Components
Package         Axial           Series         A           Capacitance         5600pF           Tolerance         ±10%           Voltage - Rated         500V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.118" Dia x 0.197" L (3.00mm x 5.00mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         A           Capacitance         5600pF           Tolerance         ±10%           Voltage - Rated         500V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.118" Dia x 0.197" L (3.00mm x 5.00mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance         5600pF           Tolerance         ±10%           Voltage - Rated         500V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.118" Dia x 0.197" L (3.00mm x 5.00mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -	Package	Axial
Tolerance ±10%  Voltage - Rated 500V  Temperature Coefficient X7R  Operating Temperature -55°C ~ 125°C  Features Ratings Applications General Purpose  Failure Rate Mounting Type Through Hole  Package / Case Axial  Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm)  Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style	Series	A
Voltage - Rated500VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.118" Dia x 0.197" L (3.00mm x 5.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Capacitance	5600pF
Temperature Coefficient  AYR  Operating Temperature  -55°C ~ 125°C  Features  - Ratings  - Applications  General Purpose  Failure Rate  - Mounting Type  Through Hole  Package / Case  Axial  Size / Dimension  Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  X7R  AyR  - Case  - Avial  - Lead Style  Axial  - Lead Syle  -  Axial  -  Lead Syle  -  Axial  -  Lead Syle  -  Axial  -  Lead Syle  -  Axial  -  Axi	Tolerance	±10%
Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Voltage - Rated	500V
Features Ratings - Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Through Hole Package / Case Axial Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm) Height - Seated (Max) - Lead Spacing - Lead Style Lead Style	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Lead Style	Ratings	-
Mounting Type Through Hole  Package / Case Axial  Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm)  Height - Seated (Max) -  Thickness (Max) -  Lead Spacing -  Lead Style	Applications	General Purpose
Package / Case Axial Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm)  Height - Seated (Max) -  Thickness (Max) -  Lead Spacing -  Lead Style -	Mounting Type	Through Hole
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -	Package / Case	Axial
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.118" Dia x 0.197" L (3.00mm x 5.00mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

#### A562K20X7RL5UAA Guarantees



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### A562K20X7RL5UAA Payment Methods



















## A562K20X7RL5UAA Shipping Methods













If you have any question about A562K20X7RL5UAA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com