



A7D50DS29A2 Information

Heisener.com

Part Number A7D50DS29A2

Manufacturer TE Connectivity AMP Connectors

Category Connectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 100POS .125

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









A7D50DS29A2 Specifications

Manufacturer Part Number A7D50DS29A2 Manufacturer TE Connectivity AMP Connectors Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 100 Card Thickness 0.054" ~ 0.071" (1.37mm ~ 1.80mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper Alloy Contact Finish Thickness 30μin (0.76μm) Contact Type - Color Black Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -55°C ~ 125°C	•	
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 100 Card Thickness 0.054" ~ 0.071" (1.37mm ~ 1.80mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper Alloy Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type - Color Black Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -55°C ~ 125°C	Manufacturer Part Number	A7D50DS29A2
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 100 Card Thickness 0.054" ~ 0.071" (1.37mm ~ 1.80mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper Alloy Contact Finish Gold Contact Type - Color Black Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -55°C ~ 125°C	Manufacturer	TE Connectivity AMP Connectors
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 100 Card Thickness 0.054" ~ 0.071" (1.37mm ~ 1.80mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper Alloy Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type - Color Black Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -55°C ~ 125°C	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 100 Card Thickness 0.054" ~ 0.071" (1.37mm ~ 1.80mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper Alloy Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type - Color Black Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -55°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions100Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper AlloyContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact Type-ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Package	-
Gender Female Number of Positions/Bay/Row - Number of Positions 100 Card Thickness 0.054" ~ 0.071" (1.37mm ~ 1.80mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper Alloy Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Cotact Type - Color Black Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -55°C ~ 125°C	Series	-
Number of Positions/Bay/Row-Number of Positions100Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper AlloyContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact Type-ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions100Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper AlloyContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact Type-ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Gender	Female
Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper AlloyContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact Type-ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Number of Positions/Bay/Row	-
Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper AlloyContact FinishGoldContact Finish Thickness30μin (0.76μm)Cotact Type-ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Number of Positions	100
Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper AlloyContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact Type-ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Card Thickness	0.054" ~ 0.071" (1.37mm ~ 1.80mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper AlloyContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact Type-ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialCopper AlloyContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact Type-ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Pitch	0.125" (3.18mm)
TerminationSolderContact MaterialCopper AlloyContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact Type-ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Features	-
Contact MaterialCopper AlloyContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact Type-ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type - Color Black Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -55°C ~ 125°C	Termination	Solder
Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type - Color Black Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -55°C ~ 125°C	Contact Material	Copper Alloy
Contact Type - Color Black Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -55°C ~ 125°C	Contact Finish	Gold
Color Black Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -55°C ~ 125°C	Contact Finish Thickness	30μin (0.76μm)
Flange Feature Top Mount Opening, Unthreaded, 0.125 " (3.18mm) Dia Operating Temperature -55 °C ~ 125 °C	Contact Type	-
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Black
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-55°C ~ 125°C
		Report errors?

A7D50DS29A2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

A7D50DS29A2 Payment Methods

































If you have any question about A7D50DS29A2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com