



AA15D1515D Information



For Reference Only

Part Number AA15D1515D

Manufacturer Delta Electronics

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER +/-15V 15W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AA15D1515D Specifications

Manufacturer Part Number AA15D1515D Manufacturer Delta Electronics Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series AA15D Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 74% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series AA15D Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 74% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Manufacturer Part Number	AA15D1515D
Package - Series AA15D Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 74% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Manufacturer	Delta Electronics
Package - Series AA15D Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 74% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Category	Power Supplies - External/Internal (Off-Board)
Series AA15D Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 74% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)		AC DC Converters
Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 74% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Package	-
Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 74% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Series	AA15D
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 74% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Туре	Enclosed
Voltage - Output 2 -15V Voltage - Output 3	Number of Outputs	2
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Site (3000V) Efficiency Operating Temperature Features DC Input Capable, Universal Input Mounting Type Size / Dimension -15V	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 74% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension -25.0 C - 20.0 C (With Decommand of the Command of the Comman	Voltage - Output 1	15V
Voltage - Output 4 Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 74% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Voltage - Output 2	-15V
Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 74% Operating Temperature -25°C ~70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 74% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation $3kV (3000V)$ Efficiency 74% Operating Temperature $-25^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating) Features DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension $3.78^{\circ}\text{L} \times 2.13^{\circ}\text{W} \times 0.92^{\circ}\text{H} (96.0\text{mm} \times 54.0\text{mm} \times 23.3\text{mm})$	Current - Output (Max)	500mA, 500mA
Voltage - Isolation 3kV (3000V) Efficiency 74% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Power (Watts)	15W
Efficiency 74% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Applications	ITE (Commercial)
Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Voltage - Isolation	3kV (3000V)
Features DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Efficiency	74%
Mounting Type DIN Rail Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Operating Temperature	-25°C ~ 70°C (With Derating)
Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Features	DC Input Capable, Universal Input
	Mounting Type	DIN Rail
Report errors?	Size / Dimension	3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)
		Report errors?

AA15D1515D Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AA15D1515D Payment Methods



















AA15D1515D Shipping Methods













If you have any question about AA15D1515D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com