



AA30D0512A Information



For Reference Only

Part Number AA30D0512A

Manufacturer Delta Electronics

Category Power Supplies - Board Mount

AC DC Converters

Description AC/DC CONVERTER 5V 12V 30W

Package 7-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AA30D0512A Specifications

Manufacturer Part Number AA30D0512A Manufacturer Delta Electronics Category Power Supplies - Board Mount AC DC Converters Package 7-DIP Module Series AA30D Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A, 1.25A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) Report errors?		
Category Power Supplies - Board Mount AC DC Converters Package 7-DIP Module Series AA30D Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A, 1.25A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm)	Manufacturer Part Number	AA30D0512A
Package 7-DIP Module Series AA30D Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A, 1.25A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm)	Manufacturer	Delta Electronics
Package 7-DIP Module Series AA30D Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A, 1.25A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm)	Category	Power Supplies - Board Mount
Series AA30D Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A, 1.25A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm)		AC DC Converters
Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A, 1.25A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm)	Package	7-DIP Module
Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A, 1.25A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm)	Series	AA30D
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A, 1.25A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm)	Туре	Enclosed
Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A, 1.25A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm)	Number of Outputs	2
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications Features OCP, OTP, OVP, SCP Operating Temperature Efficiency Mounting Type Through Hole Package / Case Size / Dimension 12V 12V	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications Features OCP, OTP, OVP, SCP Operating Temperature Efficiency Mounting Type Through Hole Package / Case Size / Dimension - Size / Dimension - Current - Output (Max) 3A, 1.25A - Current - Output (Max) 3A, 1.25A - OW OW OW Sign Applications ITE (Commercial) OCP, OTP, OVP, SCP OPPROVE, SCP (With Derating) Through Hole Through Hole 7-DIP Module Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm)	Voltage - Output 1	5V
Voltage - Output 4 Current - Output (Max) 3A, 1.25A Power (Watts) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension -25°C ~ 70°C (W x 0.85" H (89.9mm x 63.5mm x 21.7mm)	Voltage - Output 2	12V
Current - Output (Max) 3A, 1.25A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm)	Voltage - Output 4	-
Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm)	Current - Output (Max)	3A, 1.25A
Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm)	Power (Watts)	30W
Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 76% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm)	Applications	ITE (Commercial)
Efficiency 76% Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm)	Features	OCP, OTP, OVP, SCP
Mounting Type Through Hole Package / Case 7-DIP Module Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm)	Operating Temperature	-25°C ~ 70°C (With Derating)
Package / Case 7-DIP Module Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm)	Efficiency	76%
Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm)	Mounting Type	Through Hole
	Package / Case	7-DIP Module
Report errors?	Size / Dimension	3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm)
		Report errors?

AA30D0512A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AA30D0512A Payment Methods



















AA30D0512A Shipping Methods













If you have any question about AA30D0512A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com