



AA30D1212A Information



For Reference Only

Part Number AA30D1212A

Manufacturer Delta Electronics

Category Power Supplies - Board Mount

AC DC Converters

Description AC/DC CONVERTER +/-12V 30W

Package 7-DIP Module, 5 Leads

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AA30D1212A Specifications

| Manufacturer Part Number AA30D1212A Manufacturer Delta Electronics Category Power Supplies - Board Mount AC DC Converters Package 7-DIP Module, 5 Leads Series AA30D Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 -12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 80% Mounting Type Through Hole Package / Case 7-DIP Module, 5 Leads Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) | | |
|--|--------------------------|--|
| Category Power Supplies - Board Mount AC DC Converters Package 7-DIP Module, 5 Leads Series AA30D Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 -12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 80% Mounting Type Through Hole Package / Case 7-DIP Module, 5 Leads Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) | Manufacturer Part Number | AA30D1212A |
| Package 7-DIP Module, 5 Leads Series AA30D Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 -12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 80% Mounting Type Through Hole Package / Case 7-DIP Module, 5 Leads Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) | Manufacturer | Delta Electronics |
| Package 7-DIP Module, 5 Leads Series AA30D Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 -12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 80% Mounting Type Through Hole Package / Case 7-DIP Module, 5 Leads Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) | Category | Power Supplies - Board Mount |
| Series AA30D Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 -12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25 °C ~ 70 °C (With Derating) Efficiency 80% Mounting Type Through Hole Package / Case 7-DIP Module, 5 Leads Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) | | AC DC Converters |
| Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 -12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 80% Mounting Type Through Hole Package / Case 7-DIP Module, 5 Leads Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) | Package | 7-DIP Module, 5 Leads |
| Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 -12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 80% Mounting Type Through Hole Package / Case 7-DIP Module, 5 Leads Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) | Series | AA30D |
| Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 -12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 80% Mounting Type Through Hole Package / Case 7-DIP Module, 5 Leads Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) | Туре | Enclosed |
| Voltage - Output 1 12V Voltage - Output 2 -12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 80% Mounting Type Through Hole Package / Case 7-DIP Module, 5 Leads Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) | Number of Outputs | 2 |
| Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature Efficiency 80% Mounting Type Through Hole Package / Case Size / Dimension -12V -12V -12V -12V -12V -12V -12V -12 | Voltage - Input | 85 ~ 264 VAC |
| Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 80% Mounting Type Through Hole Package / Case 7-DIP Module, 5 Leads Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) | Voltage - Output 1 | 12V |
| Voltage - Output 4 Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 80% Mounting Type Through Hole Package / Case 7-DIP Module, 5 Leads Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) | Voltage - Output 2 | -12V |
| Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 80% Mounting Type Through Hole Package / Case 7-DIP Module, 5 Leads Size / Dimension 1.3A, 1.3A 1.3A 1.3A 1.3A 1.3B 1.3E 1. | Voltage - Output 3 | - |
| Power (Watts) Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 80% Mounting Type Through Hole Package / Case 7-DIP Module, 5 Leads Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) | Voltage - Output 4 | - |
| Applications ITE (Commercial) Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 80% Mounting Type Through Hole Package / Case 7-DIP Module, 5 Leads Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) | Current - Output (Max) | 1.3A, 1.3A |
| Features OCP, OTP, OVP, SCP Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 80% Mounting Type Through Hole Package / Case 7-DIP Module, 5 Leads Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) | Power (Watts) | 30W |
| Operating Temperature -25°C ~ 70°C (With Derating) Efficiency 80% Mounting Type Through Hole Package / Case 7-DIP Module, 5 Leads Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) | Applications | ITE (Commercial) |
| Efficiency 80% Mounting Type Through Hole Package / Case 7-DIP Module, 5 Leads Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) | Features | OCP, OTP, OVP, SCP |
| Mounting Type Through Hole Package / Case 7-DIP Module, 5 Leads Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) | Operating Temperature | -25°C ~ 70 °C (With Derating) |
| Package / Case 7-DIP Module, 5 Leads Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) | Efficiency | 80% |
| Size / Dimension 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) | Mounting Type | Through Hole |
| · · · · · · · · · · · · · · · · · · · | Package / Case | 7-DIP Module, 5 Leads |
| Report errors? | Size / Dimension | 3.50" L x 2.50" W x 0.85" H (89.9mm x 63.5mm x 21.7mm) |
| | | Report errors? |

AA30D1212A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AA30D1212A Payment Methods



















AA30D1212A Shipping Methods













If you have any question about AA30D1212A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com