

AAA6FZPKG

AAA6FZPKG Information

Heisener.com	 AAA6FZPKG Switchcraft Inc. Connectors, Interconnects Circular Connectors CONN PLUG 6POS INLINE SKT XLR - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



AAA6FZPKG Specifications

Manufacturer Switchcraft Inc. Category Connectors, Interconnects Circular Connectors Circular Connectors Package - Series AAA Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert XLR Mounting Type - Mounting Type Free Hanging (In-Line) Packating Type Latch Lock Orientation Keyed Orientation Silver Shell Material, Finish Zinc Die Cast, Nickel Plated Contact Finish Silver Features Backshell, Strain Relief Voltage - Rated 125VAC		
CategoryConnectors, Interconnects Circular ConnectorsPackage-Package-SeriesAAAConnector TypePlug, Female SocketsNumber of Positions6Shell Size - InsertXLRShell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderTerminationKeyedShell Material, FinishZinc Die Cast, Nickel PlatedOrientati, FinishSilverShell Material, FinishSilverFeaturesBackshell, Strain ReliefVoltage - Rated7.5A	Manufacturer Part Number	AAA6FZPKG
Circular ConnectorsPackage-SeriesAAAConnector TypePlug, Female SocketsNumber of Positions6Shell Size - InsertXLRShell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeLatch LockOrientationKeyedIngress Protection-Shell Material, FinishZinc Die Cast, Nickel PlatedContact FinishBackshell, Strain ReliefFeaturesBackshell, Strain ReliefCurrent Rating7.5A	Manufacturer	Switchcraft Inc.
Package-SeriesAAAConnector TypePlug, Female SocketsNumber of Positions6Shell Size - InsertXLRShell Size, MIL-Mounting TypeFree Hanging (In-Line)FerminationSolderPrestening TypeLach LockOrientationKeyedIngress ProtectionSilverShell Material, FinishSilverContact FinishSilverFeaturesBackshell, Strain ReliefVoltage - RatedJ25VACCurrent Rating7.5A	Category	Connectors, Interconnects
SeriesAAAConnector TypePlug, Female SocketsNumber of Positions6Shell Size - InsertXLRShell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeLatch LockOrientation-Shell Material, FinishZinc Die Cast, Nickel PlatedContact FinishSilverFeaturesBackshell, Strain ReliefVoltage - Rated125VACCurrent Rating7.5A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions6Shell Size - InsertXLRShell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeLatch LockOrientationKeyedIngress Protection-Shell Material, FinishSilverFeaturesBackshell, Strain ReliefVoltage - Rated125VACCurrent Rating7.5A	Package	-
Number of Positions6Number of PositionsKLRShell Size - InsertXLRShell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeLatch LockOrientationKeyedIngress Protection-Shell Material, FinishZinc Die Cast, Nickel PlatedContact FinishBackshell, Strain ReliefFeaturesBackshell, Strain ReliefVoltage - Rated125VACCurrent Rating7.5A	Series	AAA
Shell Size - InsertXLRShell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeLatch LockOrientationKeyedIngress Protection-Shell Material, FinishSilverFeaturesBackshell, Strain ReliefVoltage - Rated125VACCurrent Rating7.5A	Connector Type	Plug, Female Sockets
Shell Size, MIL-Mouning TypeFree Hanging (In-Line)TerminationSolderFastening TypeLatch LockOrientationKeyedIngress Protection-Shell Material, FinishZinc Die Cast, Nickel PlatedContact FinishSilverFeaturesBackshell, Strain ReliefVoltage - Rated125VACCurrent Rating7.5A	Number of Positions	б
Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeLatch LockOrientationKeyedIngress Protection-Shell Material, FinishZinc Die Cast, Nickel PlatedContact FinishSilverFeaturesBackshell, Strain ReliefVoltage - Rated125VACCurrent Rating7.5A	Shell Size - Insert	XLR
TerminationSolderFastening TypeLatch LockOrientationKeyedIngress Protection-Shell Material, FinishZinc Die Cast, Nickel PlatedContact FinishSilverFeaturesBackshell, Strain ReliefVoltage - Rated125VACCurrent Rating7.5A	Shell Size, MIL	-
Fastening TypeLatch LockOrientationKeyedIngress Protection-Shell Material, FinishZinc Die Cast, Nickel PlatedContact FinishSilverFeaturesBackshell, Strain ReliefVoltage - Rated125VACCurrent Rating7.5A	Mounting Type	Free Hanging (In-Line)
OrientationKeyedIngress Protection-Shell Material, FinishZinc Die Cast, Nickel PlatedContact FinishSilverFeaturesBackshell, Strain ReliefVoltage - Rated125VACCurrent Rating7.5A	Termination	Solder
Ingress Protection-Shell Material, FinishZinc Die Cast, Nickel PlatedContact FinishSilverFeaturesBackshell, Strain ReliefVoltage - Rated125VACCurrent Rating7.5A	Fastening Type	Latch Lock
Shell Material, FinishZinc Die Cast, Nickel PlatedContact FinishSilverFeaturesBackshell, Strain ReliefVoltage - Rated125VACCurrent Rating7.5A	Orientation	Keyed
Contact FinishSilverFeaturesBackshell, Strain ReliefVoltage - Rated125VACCurrent Rating7.5A	Ingress Protection	-
FeaturesBackshell, Strain ReliefVoltage - Rated125VACCurrent Rating7.5A	Shell Material, Finish	Zinc Die Cast, Nickel Plated
Voltage - Rated125VACCurrent Rating7.5A	Contact Finish	Silver
Current Rating 7.5A	Features	Backshell, Strain Relief
-	Voltage - Rated	125VAC
	Current Rating	7.5A
Report errors?		Report errors?

AAA6FZPKG Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

AAA6FZPKG Payment Methods



AAA6FZPKG Shipping Methods



If you have any question about AAA6FZPKG, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com