

AAO32 Information

Part Number AAO32 **Manufacturer** Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 32A 550VAC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AAO32 Specifications

Manufacturer Part NumberAAO32ManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesAAOFuse TypeCartridgeCurrent Rating32AVoltage Rating - AC550VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.539" Dia x 1.378" L (13.70mm x 35.00mm)Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series AAO Fuse Type Cartridge Current Rating 32A Voltage Rating - AC 550V Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrinal, Industrial Features - Class - Class - Class - Class - Class - Cylindrical, Blade Terminal (Bolt) Size / Dimension O.539" Dia x 1.378" L (13.70mm x 35.00mm)	Manufacturer Part Number	AAO32
Beaking Capacity @ Rated Voltage Brackage Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Series AAO Fuse Type Cartridge Current Rating 32A Voltage Rating - AC 550V Voltage Rating - DC	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesAAOFuse TypeCartridgeCurrent Rating32AVoltage Rating - AC550VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.539" Dia x 1.378" L (13.70mm x 35.00mm)	Category	Circuit Protection
SeriesAAOFuse TypeCartridgeCurrent Rating32AVoltage Rating - AC550VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.539" Dia x 1.378" L (13.70mm x 35.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 32A Voltage Rating - AC 550V Voltage Rating - DC	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 550V Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 32A 32A 32A 32A 32A 32A 32A 550V 650V 650V 650V 650V 650V 650V 6500 6500 6600 6	Series	AAO
Voltage Rating - AC Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 550V 550V 560V 560V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Class - Class Cylindrical, Blade Terminal (Bolt) Size / Dimension Cylindrical, Blade Terminal (Bolt)	Current Rating	32A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Class - Class Class Cylindrical, Blade Terminal (Bolt) Size / Dimension - Class Cylindrical, Blade Terminal (Bolt) Contact of the second contact	Voltage Rating - AC	550V
Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.539" Dia x 1.378" L (13.70mm x 35.00mm)	Voltage Rating - DC	-
Features - Class - Class - Component of the Component of	Response Time	-
Class - Approvals - Class - Coperating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.539" Dia x 1.378" L (13.70mm x 35.00mm)	Applications	Electrical, Industrial
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Bolt Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.539" Dia x 1.378" L (13.70mm x 35.00mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.539" Dia x 1.378" L (13.70mm x 35.00mm)	Class	-
Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.539" Dia x 1.378" L (13.70mm x 35.00mm)	Approvals	-
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.539" Dia x 1.378" L (13.70mm x 35.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.539" Dia x 1.378" L (13.70mm x 35.00mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 0.539" Dia x 1.378" L (13.70mm x 35.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.539" Dia x 1.378" L (13.70mm x 35.00mm)
		Report errors?

AAO32 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AAO32 Payment Methods



















AAO32 Shipping Methods













If you have any question about AAO32, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com