



AAO32M40 Information

helsener.com

For Reference Only

Part Number AAO32M40

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 32A 550VAC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AAO32M40 Specifications

Manufacturer Part NumberAAO32M40ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesAAOFuse TypeCartridgeCurrent Rating32AVoltage Rating - AC550VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.827" Dia x 2.146" L (21.00mm x 54.50mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series AAO Fuse Type Cartridge Current Rating 32A Voltage Rating - AC Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrinal, Industrial Features - Class - Class - Class - Class - Class - Class - Cylindrical, Blade Terminal (Bolt) Size / Dimension O.827" Dia x 2.146" L (21.00mm x 54.50mm)	Manufacturer Part Number	AAO32M40
Beaking Capacity @ Rated Voltage Billed Terminal (Bolt) Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) AAO Fuse Type Curret Rating Curret Rating 32A Voltage Rating - AC 550V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Specialty Fuses AAO Cartridge Cartridge 550V	Manufacturer	Eaton
Package Cylindrical, Blade Terminal (Bolt) Series AAO Fuse Type Cartridge Current Rating 32A Voltage Rating - AC 550V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Category	Circuit Protection
Series AAO Fuse Type Cartridge Current Rating 32A Voltage Rating - AC 550V Voltage Rating - DC - Response Time Applications Electrical, Industrial Features Class Approvals Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.146" L (21.00mm x 54.50mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 32A Voltage Rating - AC 550V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge S50V Cartridge 32A Saba Selva Selva Folva Selva Selv	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 550V Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 32A 32A 32A 32A 550V 650V	Series	AAO
Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 550V 550V 5600 - Characteristics - Blectrical, Industrial - Class - Class - Cylindrical, Blade Terminal (Bolt) Size / Dimension 550V Cylindrical, Blade Terminal (Bolt) 0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - 0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Current Rating	32A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Class - Class Culss Cul	Voltage Rating - AC	550V
Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Voltage Rating - DC	-
Features - Class - Class - Component of the Component of	Response Time	-
Class - Approvals - Coperating Temperature - Sereaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Applications	Electrical, Industrial
Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Class	-
Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Approvals	-
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.827" Dia x 2.146" L (21.00mm x 54.50mm)
		Report errors?

AAO32M40 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AAO32M40 Payment Methods





















AAO32M40 Shipping Methods













If you have any question about AAO32M40, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com