



### **AAO32M63 Information**

nelsener.com

For Reference Only

Part Number AAO32M63

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 32A 550VAC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **AAO32M63 Specifications**

Manufacturer Part Number     AAO32M63       Manufacturer     Eaton       Category     Circuit Protection       Electrical, Specialty Fuses       Package     Cylindrical, Blade Terminal (Bolt)       Series     AAO       Fuse Type     Cartridge       Current Rating     32A       Voltage Rating - AC     550V       Voltage Rating - DC     -       Response Time     -       Applications     Electrical, Industrial       Features     -       Class     -       Approvals     -       Operating Temperature     -       Breaking Capacity @ Rated Voltage     80kA       Mounting Type     Bolt Mount       Package / Case     Cylindrical, Blade Terminal (Bolt)       Size / Dimension     0.827" Dia x 2.146" L (21.00mm x 54.50mm)		
Category Electrical, Specialty Fuses  Package Cylindrical, Blade Terminal (Bolt) Series AAO Fuse Type Cartridge Current Rating Voltage Rating - AC Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Circuit Protection Electrical, Industrial Find Capacity @ Rated Voltage Bolt Mount Cylindrical, Blade Terminal (Bolt) Size / Dimension  Circuit Protection Electrical, Specialty Fuses  Capacity Protection  Electrical, Industrial Find Capacity Find Ca	Manufacturer Part Number	AAO32M63
PackageElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesAAOFuse TypeCartridgeCurrent Rating32AVoltage Rating - AC550VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesAAOFuse TypeCartridgeCurrent Rating32AVoltage Rating - AC550VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Category	Circuit Protection
SeriesAAOFuse TypeCartridgeCurrent Rating32AVoltage Rating - AC550VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.827" Dia x 2.146" L (21.00mm x 54.50mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 32A Voltage Rating - AC 550V  Voltage Rating - DC	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC  S50V  Voltage Rating - DC  Response Time - Applications Electrical, Industrial  Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  S2A  S50V  S12A  S2A  S2A  S2A  S2A  S2A  S2A  S2	Series	AAO
Voltage Rating - AC  Voltage Rating - DC  Response Time  - Applications  Electrical, Industrial  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension  550V  50V  50V  50V  50V  50V  50V  5	Fuse Type	Cartridge
Voltage Rating - DC  Response Time - Applications Electrical, Industrial  Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Overating Temperature Substance	Current Rating	32A
Response Time - General Features - Glass - Gla	Voltage Rating - AC	550V
Applications Electrical, Industrial  Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Voltage Rating - DC	-
Features - Class - Class - Coperating Temperature - Streaking Capacity @ Rated Voltage 80kA Bolt Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Response Time	-
Class - Approvals - Class - Coperating Temperature - Streaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Applications	Electrical, Industrial
Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  80kA  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Class	-
Breaking Capacity @ Rated Voltage 80kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Approvals	-
Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 0.827" Dia x 2.146" L (21.00mm x 54.50mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.827" Dia x 2.146" L (21.00mm x 54.50mm)
		Report errors?

### **AAO32M63 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **AAO32M63 Payment Methods**



















### **AAO32M63 Shipping Methods**













If you have any question about AAO32M63, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com