

AB40S1500D

AB40S1500D Information

"Anna "- actor heisens.co	Part Number Manufacturer Category Description Package	Delta Electronics Power Supplies - External/Internal (Off-Board) AC DC Converters AC/DC CONVERTER 15V 40W - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



AB40S1500D Specifications

Manufacturer Part NumberAB40S1500DManufacturerDelta ElectronicsCategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesAB40STypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output 42.66APower (Watts)4KV (4000V)ApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency85%Operating Temperature-40°C ~ 80°CFeaturesDI Nail				
CategoryPower Supplies - External/Internal (Off-Board) AC DC ConvertersPackage-SeriesAB40STypeEnclosedNumber of Outputs1Voltage - Output 185 ~ 264 VACVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Ou	Manufacturer Part Number	AB40S1500D		
AC DC CovertersPackage-SeriesAB40STypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)2.66APower (Watts)40WApplicationsITE (Commercial), MedicalVoltage - Isolation85%Operating Temperature-40°C ~ 80°CFeaturesDI N Rail	Manufacturer	Delta Electronics		
Package-SeriesAB40STypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Solation-Voltage - Isolation-Voltage - Isolation-Vo	Category	Power Supplies - External/Internal (Off-Board)		
SeriesAB40STypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)2.66APower (Watts)40WApplicationsTE (Commercial), MedicalVoltage - Isolation85%Operating Temperature60°C ~ 80°CFeaturesDI Input Capable, Universal InputMounting TypeDIN Rail		AC DC Converters		
TypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 155 ~ 264 VACVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Solation-Voltage - Isolation-Voltage - Isolation-Voltage - Solation-Voltage - Solation-<	Package	-		
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.66A Power (Watts) 40W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 85% Operating Temperature -40°C ~ 80°C Features DC Input Capable, Universal Input Mounting Type DIN Rail	Series	AB40S		
Voltage - Input85 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)2.66APower (Watts)40WApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency85%Operating Temperature-40°C ~ 80°CFeaturesDC Input Capable, Universal InputMounting TypeDIN Rail	Туре	Enclosed		
Voltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)2.66APower (Watts)40WApplicationsITE (Commercial), MedicalVoltage - Isolation85%Operating Temperature-40°C ~ 80°CFeaturesDC Input Capable, Universal InputMounting TypeDIN Rail	Number of Outputs	1		
Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)2.66APower (Watts)40WApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency85%Operating Temperature-40°C ~ 80°CFeaturesDIN Rail	Voltage - Input	85 ~ 264 VAC		
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)2.66APower (Watts)40WApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency85%Operating Temperature-40°C ~ 80°CFeaturesDC Input Capable, Universal InputMounting TypeDIN Rail	Voltage - Output 1	15V		
Voltage - Output 4-Current - Output (Max)2.66APower (Watts)40WApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency85%Operating Temperature-40°C ~ 80°CFeaturesDC Input Capable, Universal InputMounting TypeDIN Rail	Voltage - Output 2	-		
Current - Output (Max)2.66APower (Watts)40WApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency85%Operating Temperature-40°C ~ 80°CFeaturesDC Input Capable, Universal InputMounting TypeDIN Rail	Voltage - Output 3	-		
Power (Watts)40WApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency85%Operating Temperature-40°C ~ 80°CFeaturesDC Input Capable, Universal InputMounting TypeDIN Rail	Voltage - Output 4	-		
ApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency85%Operating Temperature-40°C ~ 80°CFeaturesDC Input Capable, Universal InputMounting TypeDIN Rail	Current - Output (Max)	2.66A		
Voltage - Isolation4kV (4000V)Efficiency85%Operating Temperature-40°C ~ 80°CFeaturesDC Input Capable, Universal InputMounting TypeDIN Rail	Power (Watts)	40W		
Efficiency85%Operating Temperature-40°C ~ 80°CFeaturesDC Input Capable, Universal InputMounting TypeDIN Rail	Applications	ITE (Commercial), Medical		
Operating Temperature-40°C ~ 80°CFeaturesDC Input Capable, Universal InputMounting TypeDIN Rail	Voltage - Isolation	4kV (4000V)		
FeaturesDC Input Capable, Universal InputMounting TypeDIN Rail	Efficiency	85%		
Mounting Type DIN Rail	Operating Temperature	$-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$		
	Features	DC Input Capable, Universal Input		
	Mounting Type	DIN Rail		
Size / Dimension 4.41" L x 2.51" W x 1.34" H (112.0mm x 63.8mm x 34.1mm)	Size / Dimension	4.41" L x 2.51" W x 1.34" H (112.0mm x 63.8mm x 34.1mm)		
Report error		Report errors?		

AB40S1500D Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

AB40S1500D Payment Methods





If you have any question about AB40S1500D, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com