



## **ABB06DHBD Information**

Heisener.com

Part Number ABB06DHBD

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 12POS 0.050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **ABB06DHBD Specifications**

Manufacturer Part Number       ABB06DHBD         Manufacturer       Sullins Connector Solutions         Category       Connectors, Interconnects         Package       -         Series       -         Card Type       Non Specified - Dual Edge         Gender       Female         Number of Positions/Bay/Row       6         Number of Positions       12         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.050" (1.27mm)         Features       -         Mounting Type       Through Hole, Right Angle         Termination       Solder, Staggered         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Hairpin Bellows         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia         Operating Temperature       -65°C ~ 150°C	TIDE OUD TIDE Specifications		
Category Card Edge Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors  Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 6 Number of Positions 12 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole, Right Angle Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer Part Number	ABB06DHBD	
Card Edge Connectors - Edgeboard Connectors  Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 6 Number of Positions 12 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole, Right Angle Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer	Sullins Connector Solutions	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 6 Number of Positions 12 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole, Right Angle Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Category	Connectors, Interconnects	
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 6 Number of Positions 12 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole, Right Angle Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia		Card Edge Connectors - Edgeboard Connectors	
Card Type Non Specified - Dual Edge Gender Female  Number of Positions/Bay/Row 6  Number of Positions 12  Card Thickness 0.062" (1.57mm)  Number of Rows 2  Pitch 0.050" (1.27mm)  Features - Mounting Type Through Hole, Right Angle  Termination Solder, Staggered  Contact Material Beryllium Copper  Contact Finish Gold  Contact Finish Thickness 10µin (0.25µm)  Contact Type Hairpin Bellows  Color Black  Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Package	-	
Gender Female  Number of Positions/Bay/Row 6  Number of Positions 12  Card Thickness 0.062" (1.57mm)  Number of Rows 2  Pitch 0.050" (1.27mm)  Features	Series	-	
Number of Positions       6         Number of Positions       12         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.050" (1.27mm)         Features       -         Mounting Type       Through Hole, Right Angle         Termination       Solder, Staggered         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Hairpin Bellows         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Type	Non Specified - Dual Edge	
Number of Positions  Card Thickness  0.062" (1.57mm)  Number of Rows  2  Pitch  0.050" (1.27mm)  Features  Mounting Type  Through Hole, Right Angle  Termination  Solder, Staggered  Contact Material  Beryllium Copper  Contact Finish  Gold  Contact Finish Thickness  10µin (0.25µm)  Contact Type  Hairpin Bellows  Color  Black  Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Gender	Female	
Card Thickness 0.062" (1.57mm)  Number of Rows 2  Pitch 0.050" (1.27mm)  Features	Number of Positions/Bay/Row	6	
Number of Rows       2         Pitch       0.050" (1.27mm)         Features       -         Mounting Type       Through Hole, Right Angle         Termination       Solder, Staggered         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Hairpin Bellows         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions	12	
Pitch       0.050" (1.27mm)         Features       -         Mounting Type       Through Hole, Right Angle         Termination       Solder, Staggered         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Hairpin Bellows         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Thickness	0.062" (1.57mm)	
Features  Mounting Type Through Hole, Right Angle  Termination Solder, Staggered  Contact Material Beryllium Copper  Contact Finish Gold Contact Finish Thickness 10μin (0.25μm)  Contact Type Hairpin Bellows  Color Black  Flange Feature  Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Rows	2	
Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Pitch	0.050" (1.27mm)	
Termination Solder, Staggered  Contact Material Beryllium Copper  Contact Finish Gold  Contact Finish Thickness 10μin (0.25μm)  Contact Type Hairpin Bellows  Color Black  Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Features	-	
Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Mounting Type	Through Hole, Right Angle	
Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Hairpin Bellows         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Termination	Solder, Staggered	
Contact Finish Thickness 10μin (0.25μm) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Material	Beryllium Copper	
Contact Type Hairpin Bellows  Color Black  Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish	Gold	
Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish Thickness	10μin (0.25μm)	
Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Type	Hairpin Bellows	
	Color	Black	
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	
	Operating Temperature	-65°C ~ 150°C	
Report errors		Report error	ors?

### **ABB06DHBD Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **ABB06DHBD Payment Methods**



















### **ABB06DHBD Shipping Methods**













If you have any question about ABB06DHBD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com