



ABB09DHAS Information

Heisener.com

Part Number ABB09DHAS

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 18POS 0.050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ABB09DHAS Specifications

Manufacturer Part Number Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 9 Number of Positions 18 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Mounting Type Through Hole, Right Angle Termination Solder, Staggered Context Material		
Category Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 9 Number of Positions 18 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Mounting Type Through Hole, Right Angle Termination Solder, Staggered	Ianufacturer Part Number	ABB09DHAS
Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 9 Number of Positions 18 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Mounting Type Through Hole, Right Angle Termination Solder, Staggered	I anufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 9 Number of Positions 18 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole, Right Angle Termination Solder, Staggered	ategory	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 9 Number of Positions 18 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole, Right Angle Termination Solder, Staggered		Card Edge Connectors - Edgeboard Connectors
Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 9 Number of Positions 18 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole, Right Angle Termination Solder, Staggered	ackage	
GenderFemaleNumber of Positions/Bay/Row9Number of Positions18Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, Staggered	eries	-
Number of Positions/Bay/Row9Number of Positions18Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, Staggered	ard Type	Non Specified - Dual Edge
Number of Positions18Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, Staggered	ender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, Staggered	umber of Positions/Bay/Row	9
Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole, Right Angle Termination Solder, Staggered	fumber of Positions	18
Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole, Right Angle Termination Solder, Staggered	ard Thickness	0.062" (1.57mm)
Features - Mounting Type Through Hole, Right Angle Termination Solder, Staggered	fumber of Rows	2
Mounting Type Through Hole, Right Angle Termination Solder, Staggered	itch	0.050" (1.27mm)
Termination Solder, Staggered	eatures	-
	Iounting Type	Through Hole, Right Angle
Contact Material	ermination	Solder, Staggered
Contact Material Beryllium Copper	Contact Material	Beryllium Copper
Contact Finish Gold	ontact Finish	Gold
Contact Finish Thickness 10μin (0.25μm)	ontact Finish Thickness	10μin (0.25μm)
Contact Type Hairpin Bellows	ontact Type	Hairpin Bellows
Color Black	olor	Black
Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	lange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	perating Temperature	-65°C ~ 150°C
Report erro		Report errors?

ABB09DHAS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ABB09DHAS Payment Methods



















ABB09DHAS Shipping Methods













If you have any question about ABB09DHAS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com