



ABB100DYRQ Information

Heisener.com

Part Number ABB100DYRQ

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 200POS .050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ABB100DYRQ Specifications

| Manufacturer Part Number ABB100DYRQ Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 100 Number of Positions 200 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Beryllium Copper Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flange Feature Straddle Mount Opening, Unthreaded, 0.078" (1.98mm) Operating Temperature -65°C ~ 150°C | ADDIOOD I NQ Specifications | |
|---|-----------------------------|---|
| Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 100 Number of Positions 200 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flange Feature Straddle Mount Opening, Unthreaded, 0.078" (1.98mm) Operating Temperature -65°C ~ 150°C | Manufacturer Part Number | ABB100DYRQ |
| Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row100Number of Positions200Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 150°C | Manufacturer | Sullins Connector Solutions |
| Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 100 Number of Positions 200 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black Flange Feature Straddle Mount Opening, Unthreaded, 0.078" (1.98mm) Operating Temperature -65°C ~ 150°C | Category | Connectors, Interconnects |
| Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row100Number of Positions200Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 150°C | | Card Edge Connectors - Edgeboard Connectors |
| Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row100Number of Positions200Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 150°C | Package | - |
| GenderFemaleNumber of Positions/Bay/Row100Number of Positions200Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 150°C | Series | - |
| Number of Positions/Bay/Row100Number of Positions200Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 150°C | Card Type | Non Specified - Dual Edge |
| Number of Positions200Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 150°C | Gender | Female |
| Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 150°C | Number of Positions/Bay/Row | 100 |
| Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 150°C | Number of Positions | 200 |
| Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 150°C | Card Thickness | 0.062" (1.57mm) |
| FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 150°C | Number of Rows | 2 |
| Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature-65°C ~ 150°C | Pitch | 0.050" (1.27mm) |
| Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever Color Black Flange Feature Straddle Mount Opening, Unthreaded, $0.078''$ ($1.98mm$) Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$ | Features | Card Extender |
| Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness 10μ in $(0.25\mu$ m)Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078 " (1.98mm)Operating Temperature -65 °C ~ 150 °C | Mounting Type | Board Edge, Straddle Mount |
| Contact FinishGoldContact Finish Thickness $10μin (0.25μm)$ Contact TypeCantileverColorBlackFlange FeatureStraddle Mount Opening, Unthreaded, 0.078" (1.98mm)Operating Temperature -65 °C ~ 150 °C | Termination | Solder |
| Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever Color Black Flange Feature Straddle Mount Opening, Unthreaded, $0.078''$ (1.98mm) Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$ | Contact Material | Beryllium Copper |
| Contact Type Color Black Flange Feature Straddle Mount Opening, Unthreaded, 0.078" (1.98mm) Operating Temperature -65°C ~ 150°C | Contact Finish | Gold |
| Color Black Flange Feature Straddle Mount Opening, Unthreaded, 0.078" (1.98mm) Operating Temperature -65°C ~ 150°C | Contact Finish Thickness | 10μin (0.25μm) |
| Flange Feature Straddle Mount Opening, Unthreaded, 0.078 " (1.98mm) Operating Temperature -65 °C ~ 150 °C | Contact Type | Cantilever |
| Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$ | Color | Black |
| | Flange Feature | Straddle Mount Opening, Unthreaded, 0.078" (1.98mm) |
| Report errors? | Operating Temperature | -65°C ~ 150°C |
| | | Report errors? |

ABB100DYRQ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ABB100DYRQ Payment Methods



















ABB100DYRQ Shipping Methods













If you have any question about ABB100DYRQ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com