



### **ABB20DYHD Information**

Heisener.com

Part Number ABB20DYHD

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 40POS 0.050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **ABB20DYHD Specifications**

Manufacturer Part Number       ABB20DYHD         Manufacturer       Sullins Connector Solutions         Category       Connectors, Interconnects         Package       -         Series       -         Card Type       Non Specified - Dual Edge         Gender       Female         Number of Positions/Bay/Row       20         Number of Positions       40         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.050" (1.27mm)         Features       -         Mounting Type       Through Hole         Termination       Solder, Staggered         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia         Operating Temperature       -65°C ~ 150°C	ADD20D TID Specifications	
Category Card Edge Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors  Package Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 20 Number of Positions 40 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer Part Number	ABB20DYHD
Card Edge Connectors - Edgeboard Connectors  Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 20 Number of Positions 40 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 20 Number of Positions 40 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 20 Number of Positions 40 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia		Card Edge Connectors - Edgeboard Connectors
Card Type	Package	-
Gender Female  Number of Positions/Bay/Row 20  Number of Positions 40  Card Thickness 0.062" (1.57mm)  Number of Rows 2  Pitch 0.050" (1.27mm)  Features  Mounting Type Through Hole  Termination Solder, Staggered  Contact Material Beryllium Copper  Contact Finish Gold  Contact Finish Thickness 10µin (0.25µm)  Contact Type Cantilever  Color Black  Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Series	-
Number of Positions       20         Number of Positions       40         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.050" (1.27mm)         Features       -         Mounting Type       Through Hole         Termination       Solder, Staggered         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Type	Non Specified - Dual Edge
Number of Positions  Card Thickness  0.062" (1.57mm)  Number of Rows  2  Pitch  0.050" (1.27mm)  Features  Mounting Type  Through Hole  Termination  Solder, Staggered  Contact Material  Beryllium Copper  Contact Finish  Gold  Contact Finish Thickness  10µin (0.25µm)  Contact Type  Cantilever  Color  Black  Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Gender	Female
Card Thickness 0.062" (1.57mm)  Number of Rows 2  Pitch 0.050" (1.27mm)  Features	Number of Positions/Bay/Row	20
Number of Rows       2         Pitch       0.050" (1.27mm)         Features       -         Mounting Type       Through Hole         Termination       Solder, Staggered         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions	40
Pitch       0.050" (1.27mm)         Features       -         Mounting Type       Through Hole         Termination       Solder, Staggered         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Thickness	0.062" (1.57mm)
Features  Mounting Type Through Hole Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black Flange Feature	Number of Rows	2
Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Pitch	0.050" (1.27mm)
Termination Solder, Staggered  Contact Material Beryllium Copper  Contact Finish Gold  Contact Finish Thickness 10μin (0.25μm)  Contact Type Cantilever  Color Black  Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Features	-
Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Mounting Type	Through Hole
Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Termination	Solder, Staggered
Contact Finish Thickness  10μin (0.25μm)  Contact Type  Cantilever  Color  Black  Flange Feature  Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Material	Beryllium Copper
Contact Type Cantilever  Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish	Gold
Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Type	Cantilever
	Color	Black
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia
	Operating Temperature	-65°C ~ 150°C
Report errors		Report errors?

#### **ABB20DYHD Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **ABB20DYHD Payment Methods**



















### **ABB20DYHD Shipping Methods**













If you have any question about ABB20DYHD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com