



ABB60DHRT Information

Heisener.com

Part Number ABB60DHRT

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 120POS .050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ABB60DHRT Specifications

Manufacturer Part Number ABB60DHRT Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 60 Number of Positions 120 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 150°C	ADDOODIIKI Specifications	
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 60 Number of Positions 120 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 150°C	Manufacturer Part Number	ABB60DHRT
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 60 Number of Positions 120 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row60Number of Positions120Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row60Number of Positions120Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row60Number of Positions120Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Package	-
GenderFemaleNumber of Positions/Bay/Row60Number of Positions120Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Series	-
Number of Positions/Bay/Row60Number of Positions120Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	60
Number of Rows2Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Number of Positions	120
Pitch0.050" (1.27mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Number of Rows	2
Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness 10μ in $(0.25\mu$ m)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature -65 °C ~ 150 °C	Pitch	0.050" (1.27mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Features	Card Extender
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness 10μ in $(0.25\mu$ m)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature -65° C ~ 150° C	Mounting Type	Board Edge, Straddle Mount
Contact Finish Contact Finish Thickness 10μ in $(0.25\mu$ m) Contact Type Hairpin Bellows Color Black Flunge Feature Flush Mount, Top Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 150°C	Termination	Solder
Contact Finish Thickness 10μ in $(0.25\mu$ m) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Threaded Insert, 4-40 Operating Temperature -65° C $\sim 150^{\circ}$ C	Contact Material	Beryllium Copper
Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Threaded Insert, 4-40 Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Finish	Gold
Color Black Flange Feature Flush Mount, Top Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 150°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Flush Mount, Top Opening, Threaded Insert, 4-40 Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Type	Hairpin Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Black
	Flange Feature	Flush Mount, Top Opening, Threaded Insert, 4-40
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

ABB60DHRT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ABB60DHRT Payment Methods



















ABB60DHRT Shipping Methods













If you have any question about ABB60DHRT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com