

ABB75DHHR

ABB75DHHR Information

Heisener.com	 ABB75DHHR Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 150POS .050 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ABB75DHHR Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row75Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact FinishSolder, StaggeredContact Finish ThicknessGoldContact TypeInjuin CopperContact TypeJojin 0.25µm)Contact TypeBackContact TypeBackContact TypeBackContact TypeSolder, StaggeredContact TypeSolder, StaggeredContact TypeBackContact TypeSolder, StaggeredContact TypeSolder, Stage	-	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row75Number of Positions0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact Finish ThicknessIoµin (0.25µm)Contact TypeHairpin BellowsContact TypeBackColorBlackFlange Feature-<	Manufacturer Part Number	ABB75DHHR
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row75Number of Positions150Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsContact TypeBackFlange Feature-Operating Temperature-50°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row75Number of Positions150Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-55°C ~ 150°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row75Number of Positions150Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact Finish ThicknessSolder, StaggeredContact Finish ThicknessIpµin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row75Number of Positions150Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.500" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHarpin BellowsColorBlackFaqueree-Operating Temperature-65°C ~ 150°C	Package	-
GenderFemaleNumber of Positions/Bay/Row75Number of Positions150Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSolder, StaggeredContact MaterialGoldContact FinishGoldContact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Series	-
Number of Positions/Bay/Row75Number of Positions150Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleContact MaterialSolder, StaggeredContact FinishGoldContact Type10µin (0.25µm)Contact TypeBackFlange Feature-Operating Temperature-50°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions 150 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Through Hole Contact Material Solder, Staggered Contact Finish Gold Contact Finish Thickness Ioµin (0.25µm) Contact Type Hairpin Bellows Color Black Flange Feature - Operating Temperature -65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	75
Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions	150
Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)ColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
FeaturesBoard LockMounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish ThicknessI/µin (0.25µm)Contact TypeBlackFlange Feature-Operating Temperatures-65°C ~ 150°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Pitch	0.050" (1.27mm)
TerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Features	Board Lock
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Termination	Solder, Staggered
Contact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Contact Material	Beryllium Copper
Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Contact Finish	Gold
ColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature-Operating Temperature-65°C ~ 150°C	Contact Type	Hairpin Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	$-65^{\circ}C \sim 150^{\circ}C$
		Report errors?

ABB75DHHR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ABB75DHHR Payment Methods



ABB75DHHR Shipping Methods



If you have any question about ABB75DHHR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com