



ABB90DYFR Information

Heisener.com

Part Number ABB90DYFR

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 180POS .050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ABB90DYFR Specifications

| Manufacturer Part Number ABB90DYFR Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 90 Number of Positions 180 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Surface Mount Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C | ADD/0D II K Specifications | |
|---|-----------------------------|---|
| Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 90 Number of Positions 180 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Surface Mount Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C | Manufacturer Part Number | ABB90DYFR |
| Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 90 Number of Positions 180 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Surface Mount Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C | Manufacturer | Sullins Connector Solutions |
| Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 90 Number of Positions 180 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Surface Mount Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C | Category | Connectors, Interconnects |
| Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 90 Number of Positions 180 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Surface Mount Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C | | Card Edge Connectors - Edgeboard Connectors |
| Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 90 Number of Positions 180 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Surface Mount Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C | Package | - |
| Gender Female Number of Positions/Bay/Row 90 Number of Positions 180 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Surface Mount Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65°C ~ 150°C | Series | - |
| Number of Positions/Bay/Row Number of Positions 180 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features Board Lock Mounting Type Surface Mount Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Black Flange Feature Operating Temperature -65°C ~ 150°C | Card Type | Non Specified - Dual Edge |
| Number of Positions180Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C | Gender | Female |
| Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C | Number of Positions/Bay/Row | 90 |
| Number of Rows2Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C | Number of Positions | 180 |
| Pitch0.050" (1.27mm)FeaturesBoard LockMounting TypeSurface MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C | Card Thickness | 0.062" (1.57mm) |
| FeaturesBoard LockMounting TypeSurface MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C | Number of Rows | 2 |
| Mounting TypeSurface MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C | Pitch | 0.050" (1.27mm) |
| Termination Solder Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color Black Flange Feature - Operating Temperature Solder Color Beryllium Copper Cold Gold Contact Type Cantilever Cantilever - Color Color | Features | Board Lock |
| Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C | Mounting Type | Surface Mount |
| Contact Finish Contact Finish Thickness 10μ in $(0.25\mu$ m) Contact Type Cantilever Color Black Flange Feature Operating Temperature Gold $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$ | Termination | Solder |
| Contact Finish Thickness 10μ in $(0.25\mu$ m) Contact Type Cantilever Color Black Flange Feature - Operating Temperature -65° C $\sim 150^{\circ}$ C | Contact Material | Beryllium Copper |
| Contact Type Color Black Flange Feature - Operating Temperature -65°C ~ 150°C | Contact Finish | Gold |
| Color Black Flange Feature - Operating Temperature -65°C ~ 150°C | Contact Finish Thickness | 10μin (0.25μm) |
| Flange Feature - Generating Temperature -65°C ~ 150 °C | Contact Type | Cantilever |
| Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$ | Color | Black |
| | Flange Feature | - |
| | Operating Temperature | -65°C ~ 150°C |
| Report errors? | | Report errors? |

ABB90DYFR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ABB90DYFR Payment Methods



















ABB90DYFR Shipping Methods













If you have any question about ABB90DYFR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com