



ABC05DREH Information

Heisener.com

Part Number ABC05DREH

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 10POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ABC05DREH Specifications

Manufacturer Part Number ABC05DREH Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Scries - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 5 Number of Positions 10 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	ADCOSDICENT Specifications		
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 5 Number of Positions 10 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Manufacturer Part Number	ABC05DREH	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 5 Number of Positions 10 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Manufacturer	Sullins Connector Solutions	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 5 Number of Positions 10 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Category	Connectors, Interconnects	
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 5 Number of Positions 10 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Series	-	
Number of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Type	Non Specified - Dual Edge	
Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	5	
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions	10	
Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)	
Features Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Number of Rows	2	
Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Pitch	0.100" (2.54mm)	
Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125 " ($3.18mm$) Dia Operating Temperature -65 °C ~ 150 °C	Features	-	
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness 10μ in $(0.25\mu$ m)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125 " $(3.18$ mm) DiaOperating Temperature -65 °C ~ 150 °C	Mounting Type	Panel Mount	
Contact FinishGoldContact Finish Thickness $10μin (0.25μm)$ Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, $0.125" (3.18mm)$ DiaOperating Temperature -65 °C ~ 150 °C	Termination	Solder Eyelet(s)	
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, $0.125''$ ($3.18mm$) Dia Operating Temperature $-65^{\circ}C \sim 150^{\circ}C$	Contact Material	Beryllium Copper	
Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Contact Finish	Gold	
Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature -65 °C ~ 150 °C	Contact Finish Thickness	10μin (0.25μm)	
Flange Feature Top Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature -65 °C ~ 150 °C	Contact Type	Full Bellows	
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Green	
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 150°C	
X .			Report errors?

ABC05DREH Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ABC05DREH Payment Methods



















ABC05DREH Shipping Methods













If you have any question about ABC05DREH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com