



### **ABC10DRTS-S93 Information**

Heisener.com

Part Number ABC10DRTS-S93

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 20POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **ABC10DRTS-S93 Specifications**

| Manufacturer Part Number         ABCIODRTS-S93           Manufacturer         Sullins Connector Solutions           Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         10           Number of Positions         20           Card Thickness         0.093" (2.36mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Full Bellows           Color         Green           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C           Report errors? | •                           |   |
|--|-----------------------------|---|
| Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         10           Number of Positions         20           Card Thickness         0.093" (2.36mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Full Bellows           Color         Green           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C  | Manufacturer Part Number    | ABC10DRTS-S93                                       |
| Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         10           Number of Positions         20           Card Thickness         0.093" (2.36mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Type         Full Bellows           Color         Green           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C   | Manufacturer                | Sullins Connector Solutions                         |
| Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         10           Number of Positions         20           Card Thickness         0.093" (2.36mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Full Bellows           Color         Green           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C   | Category                    | Connectors, Interconnects                           |
| Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         10           Number of Positions         20           Card Thickness         0.093" (2.36mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Full Bellows           Color         Green           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C   |                             | Card Edge Connectors - Edgeboard Connectors         |
| Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         10           Number of Positions         20           Card Thickness         0.093" (2.36mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Full Bellows           Color         Green           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C  | Package                     | -   |
| Gender         Female           Number of Positions/Bay/Row         10           Number of Positions         20           Card Thickness         0.093" (2.36mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Cotact Type         Full Bellows           Color         Green           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C   | Series                      | -   |
| Number of Positions/Bay/Row10Number of Positions20Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C   | Card Type                   | Non Specified - Dual Edge                           |
| Number of Positions  Card Thickness  0.093" (2.36mm)  Number of Rows  2  Pitch  0.100" (2.54mm)  Features  -  Mounting Type  Through Hole  Termination  Solder  Contact Material  Beryllium Copper  Contact Finish  Gold  Contact Finish Thickness  10µin (0.25µm)  Contact Type  Full Bellows  Color  Flange Feature  Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -65°C ~ 150°C   | Gender                      | Female  |
| Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C   | Number of Positions/Bay/Row | 10  |
| Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C  | Number of Positions         | 20  |
| Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C   | Card Thickness              | 0.093" (2.36mm)                                     |
| Features  Mounting Type Through Hole  Termination Solder  Contact Material Beryllium Copper  Contact Finish Contact Finish Thickness 10μin (0.25μm)  Contact Type Full Bellows  Color Green  Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -65°C ~ 150°C  | Number of Rows              | 2   |
| Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C  | Pitch                       | 0.100" (2.54mm)                                     |
| TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature $-65$ °C ~ 150°C   | Features                    | -   |
| Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10\mu$ in $(0.25\mu$ m)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, $0.125$ " $(3.18$ mm) DiaOperating Temperature $-65$ °C ~ $150$ °C  | Mounting Type               | Through Hole  |
| Contact Finish  Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type  Full Bellows  Color  Green  Flange Feature  Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -65°C ~ 150°C  | Termination                 | Solder  |
| Contact Finish Thickness $10\mu in (0.25\mu m)$<br>Contact Type Full Bellows<br>Color Green<br>Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia<br>Operating Temperature $-65^{\circ}C \sim 150^{\circ}C$  | Contact Material            | Beryllium Copper                                    |
| Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C   | Contact Finish              | Gold  |
| Color Green  Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 150°C   | Contact Finish Thickness    | 10μin (0.25μm)                                      |
| Flange Feature Side Mount Opening, Unthreaded, $0.125$ " (3.18mm) Dia Operating Temperature $-65$ °C $\sim 150$ °C   | Contact Type                | Full Bellows  |
| Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$   | Color                       | Green   |
|  | Flange Feature              | Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia |
| Report errors?   | Operating Temperature       | -65°C ~ 150°C                                       |
|  |                             | Report errors?                                      |

#### **ABC10DRTS-S93 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **ABC10DRTS-S93 Payment Methods**



















### **ABC10DRTS-S93 Shipping Methods**













If you have any question about ABC10DRTS-S93, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com