

ABC13HEYN

ABC13HEYN Information

Heisener.com	Part Number Manufacturer Category Description Package	ABC13HEYN Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 13POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ABC13HEYN Specifications

ManufacturerSullins Connector SolutionsCardegerConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting Type1Gondart FinishSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeGuil (25µm)Contact TypeGuil (25µm)Contact Finish ThicknessSolderContact Finish ThicknessGuil (25µm)Contact TypeGuil (25µm)Contact TypeGuil (25µm)Contact Finish ThicknessSolderContact Finish ThicknessSolderContact TypeCantileverFange Feature-Fange FeatureSolderColor-Color<	-	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions/Bay/Row0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessIQuin (0.25µm)Contact Finish ThicknessIQuin (0.25µm)Contact TypeCantileverContact TypeCantileverContact Finish ThicknessIQuin (0.25µm)Contact TypeCantileverColor-Flange Feature-Color-Flange Feature-Operating Temperature65°C ~ 150°C	Manufacturer Part Number	ABC13HEYN
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions13Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10µin (0.25µm)Contact TypeCantileverContact TypeCantileverContact TypeCantileverContact Type-Color-Flange Feature-Operating Temperature-65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions13Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10µin (0.25µm)Contact TypeCantileverContact TypeCantileverContact TypeCantileverContact Type-Flange Feature-Operating Temperature-50°C ~ 150°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions/Bay/Row13Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact Finish ThicknessSolderContact Finish Thickness10µin (0.25µm)Contact TypeGoldContact Finish ThicknessGoldContact TypeCantileverColor-Flange Feature-Operating Temperature65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions13Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish ThicknessIContact TypeCantileverColtact TypeCantileverFlange Feature-Operating Temperature65°C ~ 150°C	Package	-
GenderFemaleNumber of Positions/Bay/Row-Number of Positions13Card Thickness0.062" (1.57mm)Number of Rows1Number of Rows0.100" (2.54mm)Pitch0.100" (2.54mm)Features-Mounting TypeMough HoleContact MaterialSolderContact FinishGoldContact Finish ThicknessIupin (0.25µm)Contact TypeCantileverFlange Feature-Porating Temperature6°C ~ 150°C	Series	-
Number of Positions/Bay/Row-Number of Positions13Card Thickness0.062" (1.57mm)Number of Rows1Number of Rows0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact TypeOupin (0.25µm)Color-Flange Feature-Poperating Temperature-Operating Temperature-Contact Sing	Card Type	Non Specified - Dual Edge
Number of Positions13Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialGoldContact Finish ThicknessIupin (0.25µm)Contact TypeCantileverFlange Feature-Poperating Temperature65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeCantileverColor-Flange Feature-Operating Temperature65°C ~ 150°C	Number of Positions/Bay/Row	-
Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions	13
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Color-Color-Flange Feature-Operating Temperature65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact Type-Color-Flange Feature-Operating Temperature-65°C ~ 150°C	Number of Rows	1
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 150°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 150°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 150°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 150°C	Termination	Solder
Contact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 150°C	Contact Material	Beryllium Copper
Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 150°C	Contact Finish	Gold
Color - Flange Feature - Operating Temperature -65°C ~ 150°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature-Operating Temperature-65°C ~ 150°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	-
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

ABC13HEYN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ABC13HEYN Payment Methods



ABC13HEYN Shipping Methods



If you have any question about ABC13HEYN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com