

ABC15DKRI-S1243

ABC15DKRI-S1243 Information

Heisener.com	 ABC15DKRI-S1243 Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 30POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ABC15DKRI-S1243 Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCard IlieverContact TypeCantileverContact TypeContact TypeContact Finish Thickness10µin (0.25µm)Contact Finish ThicknessFortileverContact TypeCantileverContact TypeCantileverContact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Contact TypeCard IliverContact TypeGoldContact TypeCantileverContact TypeCantileverContact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-50°C ~ 150°C	Manufacturer Part Number	ABC15DKRI-S1243
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialGoldContact Finish Thickness10/uin (0.25µm)Contact Finish Thickness10/uin (0.25µm)Contact TypeCantileverContact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialGoldContact FinishGoldContact Finish Thickness10/uin (0.25µm)Contact TypeCantileverContact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-55°C ~ 150°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions/Bay/Row30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesGard ExtenderMounting TypeBoard Edge, Straddle MountContact Finish ThicknessGoldContact Finish ThicknessJupin (0.25µm)Contact TypeGoldContact TypeGoldContact TypeGoldContact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialGoldContact Finish Thickness10µin (0.25µm)Contact TypeCard IleverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-55°C ~ 150°C	Package	-
GenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Series	-
Number of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-55°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions 30 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Gold Contact Finish Thickness Ioµin (0.25µm) Contact Type Cardilever Color - Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	15
Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Number of Positions	30
Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Color-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish ThicknessI0µin (0.25µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Number of Rows	2
Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Features	Card Extender
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Mounting Type	Board Edge, Straddle Mount
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Termination	Solder
Contact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Contact Material	Beryllium Copper
Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Contact Finish	Gold
Color - Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 150°C	Contact Finish Thickness	10µin (0.25µm)
Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	-
	Flange Feature	Top Mount Opening, Threaded Insert, 4-40
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

ABC15DKRI-S1243 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ABC15DKRI-S1243 Payment Methods





If you have any question about ABC15DKRI-S1243, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com