



### **ABC18DEYH Information**

Heisener.com

Part Number ABC18DEYH

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 36POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **ABC18DEYH Specifications**

Manufacturer Part Number         ABC18DEYH           Manufacturer         Sullins Connector Solutions           Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         18           Number of Positions         36           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Contact Material         Beryllium Copper           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Cantilever           Color         -           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C	ABCIODE III Specifications	
Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         18           Number of Positions         36           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Type         Cantilever           Color         -           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C	Manufacturer Part Number	ABC18DEYH
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         18           Number of Positions         36           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Cantilever           Color         -           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         18           Number of Positions         36           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Cantilever           Color         -           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C	Category	Connectors, Interconnects
Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         18           Number of Positions         36           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Cantilever           Color         -           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Package	-
Gender         Female           Number of Positions/Bay/Row         18           Number of Positions         36           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Cantilever           Color         -           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C	Series	-
Number of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions       36         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.100" (2.54mm)         Features       -         Mounting Type       Through Hole         Termination       Solder         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       10µin (0.25µm)         Contact Type       Cantilever         Color       -         Flange Feature       Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia         Operating Temperature       -65°C ~ 150°C	Gender	Female
Card Thickness 0.062" (1.57mm)  Number of Rows 2  Pitch 0.100" (2.54mm)  Features  Mounting Type Through Hole  Termination Solder  Contact Material Beryllium Copper  Contact Finish Gold  Contact Finish Thickness 10µin (0.25µm)  Contact Type Cantilever  Color  Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 150°C	Number of Positions/Bay/Row	18
Number of Rows2Pitch $0.100"$ (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10\mu$ in (0.25 $\mu$ m)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature $-65$ °C ~ $150$ °C	Number of Positions	36
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
Features  Mounting Type Through Hole  Termination Solder  Contact Material Beryllium Copper  Contact Finish Contact Finish Thickness 10μin (0.25μm)  Contact Type Cantilever  Color - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10\mu$ in $(0.25\mu$ m)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature $-65$ °C ~ $150$ °C	Pitch	0.100" (2.54mm)
Termination Solder  Contact Material Beryllium Copper  Contact Finish Gold  Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever  Color -  Flange Feature Top Mount Opening, Unthreaded, $0.125$ " ( $3.18mm$ ) Dia  Operating Temperature $-65$ °C ~ $150$ °C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10\mu$ in $(0.25\mu$ m)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, $0.125$ " $(3.18$ mm) DiaOperating Temperature $-65$ °C ~ $150$ °C	Mounting Type	Through Hole
Contact Finish  Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type  Cantilever  Color  -  Flange Feature  Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -65°C ~ 150°C	Termination	Solder
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever $-$ Color $-$ Flange Feature Top Mount Opening, Unthreaded, $0.125''$ ( $3.18mm$ ) Dia $-65^{\circ}$ C $\sim 150^{\circ}$ C	Contact Material	Beryllium Copper
Contact Type Cantilever  Color -  Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 150°C	Contact Finish	Gold
Color -  Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 150°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Top Mount Opening, Unthreaded, $0.125$ " (3.18mm) Dia Operating Temperature $-65$ °C $\sim 150$ °C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	-
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

### **ABC18DEYH Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **ABC18DEYH Payment Methods**



















# **ABC18DEYH Shipping Methods**













If you have any question about ABC18DEYH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com