

ABC18DREH

ABC18DREH Information

Heisener.com	 ABC18DREH Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 36POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ABC18DREH Specifications

Manufacturer Part Number ABC18DREH Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Cated Edge Connectors - Edgeboard Connectors Cated Edge Connectors - Edgeboard Connectors Package - Stries - Grand Type - Gender Non Specified - Dual Edge Number of Positions/Bay/Row 18 Number of Positions/Bay/Row 36 Number of Positions 36 Striks 0.062" (1.57mm) Number of Rows 2 Pactures . Mounting Type Panel Mount Young Type Solder Eyelet(s) Contact Material Solder Symmet Contact Finish Thickness Gold Contact Finish Thickness Goldow Contact Finish Thickness Jupi Bellows Contact Finish Thickness Iupi Bellows Color Green Falage Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Color Solder Sole Sole Sole Sole Sole Sole Sole Sole	_	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Number of Rows0.100" (2.54mm)Features-Nounting TypePanel MountContact MaterialSolder Eyels(s)Contact FinishGoldContact Finish ThicknessIpµi (0.25µm)Contact TypeFull BellowsContact TypeGreenFalage FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Manufacturer Part Number	ABC18DREH
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type9ale MountContact MaterialSolder Eyelet(s)Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHallellowsContact Type10µin (0.25µm)Contact Type10µin (0.25µm)Contact Type10µin (0.25µm)Contact Type10µin (0.25µm)Contact Type10µin (0.25µm)Contact Type10µin (0.25µm)Contact Type50/cenaContact Type10µin (0.25µm)Contact Type60/cenaContact Type50°C > 10°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Card Thickness0.602" (1.57mm)Card Thickness0.602" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact FinishGoldContact Finish ThicknessJuin (0.25µm)Contact TypeFull BellowsContact TypeFull BellowsContact TypeGoldContact TypeGreenFlange FeatureContact Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature65°C ~ 150°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish Thickness10µin (0.25µm)Contact Finish ThicknessGoldContact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact Finish ThicknessGoldContact Finish ThicknessIujuin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Package	-
GenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 150°C	Series	-
Number of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type9Ponel MountSolder Eyelet(s)Contact MaterialGoldContact Finish Thickness0.10/10.25µm)Contact TypeHull BellowsColorGreenFlange Feature-Ponel Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-Sol°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions 36 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Gold Contact Finish Ioµin (0.25µm) Contact Finish Thickness Ioµin (0.25µm) Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeFull BellowsColorGreenFlange FeatureSoly Contact Oper Sing Sing Sing Sing Sing Sing Sing Sing	Number of Positions/Bay/Row	18
Number of Rows2Nich0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions	36
Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeJuµin (0.25µm)ColorFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish ThicknessJuµin (0.25µm)Contact TypeFul BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature-65°C ~ 150°C	Number of Rows	2
Mounting TypePanel MountMounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Pitch	0.100" (2.54mm)
TerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Mounting Type	Panel Mount
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Termination	Solder Eyelet(s)
Contact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Contact Material	Beryllium Copper
Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Contact Finish	Gold
ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Contact Finish Thickness	10μin (0.25μm)
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Green
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	$-65^{\circ}C \sim 150^{\circ}C$
		Report errors?

ABC18DREH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ABC18DREH Payment Methods



ABC18DREH Shipping Methods



If you have any question about ABC18DREH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com