

## ABC18DRTF

est a Quote

#### **ABC18DRTF Information**

Part Number	ABC18DRTF	
Manufacturer	Sullins Connector Solutions	
Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	
Description	CONN EDGE DUAL FMALE 36POS 0.100	
Package	-	
	For the pricing/inventory/lead time, please contact	
	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	
	Manufacturer Category Description	Manufacturer Sullins Connector Solutions   Category Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors   Description CONN EDGE DUAL FMALE 36POS 0.100   Package -   For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **ABC18DRTF Specifications**

ManufacturerSullins Connectors SolutionsCardegoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions/Bay/Row36Card Tyickness0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Features-Mounting TypeSolderContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessJujin (0.25µm)Contact TypeFull BellowsContact TypeGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-5°C ~ 150°C	-		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Features-Mounting Type17nough HoleContact FinishSolderContact Finish Thickness0.010° (2.54mm)Contact TypeGuid Contact SectionContact TypeSolderContact Finish ThicknessGuidContact TypeFull BellowsColorGreenFlange Feature-Operating Temperature65° < 150°C	Manufacturer Part Number	ABC18DRTF	
AndCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness19µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Mounting Type-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeSolderContact TypeSolderContact Type50/to 25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeGoldContact TypeFull BellowsContact TypeFull BellowsColorGreenFlange Feature-50°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact TypeFull BellowsContact TypeFull BellowsColorGreenFlange Feature-So°C ~ 150°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-55°C ~ 150°C	Series	-	
Number of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-55°C ~ 150°C	Card Type	Non Specified - Dual Edge	
Number of Positions   36     Card Thickness   0.062" (1.57mm)     Number of Rows   2     Pitch   0.100" (2.54mm)     Features   -     Mounting Type   Through Hole     Termination   Solder     Contact Material   Beryllium Copper     Contact Finish   Gold     Contact Finish Thickness   10µin (0.25µm)     Contact Type   Full Bellows     Color   Green     Flange Feature   Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia     Operating Temperature   -65°C ~ 150°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessIoµin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-55°C ~ 150°C	Number of Positions/Bay/Row	18	
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleMounting TypeSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions	36	
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Number of Rows	2	
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Pitch	0.100" (2.54mm)	
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Features	-	
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Mounting Type	Through Hole	
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Termination	Solder	
Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Contact Material	Beryllium Copper	
Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Contact Finish	Gold	
ColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Contact Finish Thickness	10µin (0.25µm)	
Flange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Contact Type	Full Bellows	
Operating Temperature $-65^{\circ}C \sim 150^{\circ}C$	Color	Green	
	Flange Feature	Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 150°C	
			Report errors?

#### **ABC18DRTF Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE SUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ABC18DRTF Payment Methods**





If you have any question about ABC18DRTF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com