



ABC44DTMS Information

Heisener.com

Part Number ABC44DTMS

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 88POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ABC44DTMS Specifications

Manufacturer Part Number ABC44DTMS Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 44 Number of Positions 88 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Thickness 10µin (0.25µm) Contact Type Loop Bellows Cotor - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	ABC44D IMS Specifications	
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 44 Number of Positions 88 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Type Loop Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Manufacturer Part Number	ABC44DTMS
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact TypeLoop BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 44 Number of Positions 88 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Loop Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 44 Number of Positions 88 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Loop Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Cotact TypeLoop BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Package	-
Gender Female Number of Positions/Bay/Row 44 Number of Positions 88 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Loop Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Series	-
Number of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	44
Number of Rows2Pitch $0.100"$ (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeLoop BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, $0.125"$ (3.18mm) DiaOperating Temperature -65° C ~ 150° C	Number of Positions	88
Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
Features Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 10μin (0.25μm) Contact Type Loop Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Number of Rows	2
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeLoop BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature -65 °C ~ 150 °C	Pitch	0.100" (2.54mm)
Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Loop Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeLoop BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, $0.125''$ ($3.18mm$) DiaOperating Temperature -65° C ~ 150° C	Mounting Type	Through Hole, Right Angle
Contact Finish Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Loop Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Termination	Solder
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Loop Bellows Color - Side Mount Opening, Unthreaded, $0.125''$ ($3.18mm$) Dia Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Material	Beryllium Copper
Contact Type Loop Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Contact Finish	Gold
Color - Side Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature - 65 °C ~ 150 °C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Side Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature -65 °C ~ 150 °C	Contact Type	Loop Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	-
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

ABC44DTMS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ABC44DTMS Payment Methods



















ABC44DTMS Shipping Methods













If you have any question about ABC44DTMS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com