



### **ABC550-1T15 Information**

Part Number ABC550-1T15

Manufacturer Bel Power Solutions

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

**Description** AC/DC CONVERTER 15V 150/550W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ABC550-1T15 Specifications**

Manufacturer Part Number         ABC550-1T15           Manufacturer         Bel Power Solutions           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         ABC550           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         7.33A           Power (Watts)         150W (550W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         90%           Operating Temperature         -40°C ~ 70°C           Features         DC Input Capable, PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	•	
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         ABC550           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         7.33A           Power (Watts)         150W (550W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         90%           Operating Temperature         -40°C ~ 70°C           Features         DC Input Capable, PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount	Manufacturer Part Number	ABC550-1T15
Package         -           Series         ABC550           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         7.33A           Power (Watts)         150W (550W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         90%           Operating Temperature         -40°C ~ 70°C           Features         DC Input Capable, PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount	Manufacturer	Bel Power Solutions
Package         -           Series         ABC550           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         7.33A           Power (Watts)         150W (550W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         90%           Operating Temperature         -40°C ~ 70°C           Features         DC Input Capable, PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount	Category	Power Supplies - External/Internal (Off-Board)
SeriesABC550TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)7.33APower (Watts)150W (550W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency90%Operating Temperature-40°C ~ 70°CFeaturesDC Input Capable, PFC, Standby Output, Universal InputMounting TypeChassis Mount		AC DC Converters
TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)7.33APower (Watts)150W (550W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency90%Operating Temperature-40°C ~ 70°CFeaturesDC Input Capable, PFC, Standby Output, Universal InputMounting TypeChassis Mount	Package	-
Number of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)7.33APower (Watts)150W (550W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency90%Operating Temperature-40°C ~ 70°CFeaturesDC Input Capable, PFC, Standby Output, Universal InputMounting TypeChassis Mount	Series	ABC550
Voltage - Input90 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)7.33APower (Watts)150W (550W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency90%Operating Temperature-40°C ~ 70°CFeaturesDC Input Capable, PFC, Standby Output, Universal InputMounting TypeChassis Mount	Type	Open Frame
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 7.33A Power (Watts) 150W (550W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 90% Operating Temperature -40°C ~ 70°C Features DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  -  Voltage - Output 4  -  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  Operating Temperature  -40°C ~ 70°C  Features  DC Input Capable, PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  90%  Operating Temperature  -40°C ~ 70°C  Features  DC Input Capable, PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount	Voltage - Output 1	15V
Voltage - Output 4  Current - Output (Max)  7.33A  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  90%  Operating Temperature  -40°C ~ 70°C  Features  DC Input Capable, PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount	Voltage - Output 2	-
Current - Output (Max)  7.33A  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  90%  Operating Temperature  -40°C ~ 70°C  Features  DC Input Capable, PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount	Voltage - Output 3	-
Power (Watts)150W (550W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency90%Operating Temperature-40°C ~ 70°CFeaturesDC Input Capable, PFC, Standby Output, Universal InputMounting TypeChassis Mount	Voltage - Output 4	-
Applications ITE (Commercial)  Voltage - Isolation 3kV (3000V)  Efficiency 90%  Operating Temperature -40°C ~ 70°C  Features DC Input Capable, PFC, Standby Output, Universal Input  Mounting Type Chassis Mount	Current - Output (Max)	7.33A
Voltage - Isolation $3kV$ (3000V)Efficiency $90\%$ Operating Temperature $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$ FeaturesDC Input Capable, PFC, Standby Output, Universal InputMounting TypeChassis Mount	Power (Watts)	150W (550W Forced Air)
Efficiency 90%  Operating Temperature $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Features DC Input Capable, PFC, Standby Output, Universal Input  Mounting Type Chassis Mount	Applications	ITE (Commercial)
Operating Temperature $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Features DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount	Voltage - Isolation	3kV (3000V)
Features DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount	Efficiency	90%
Mounting Type Chassis Mount	Operating Temperature	-40°C ~ 70°C
	Features	DC Input Capable, PFC, Standby Output, Universal Input
Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Mounting Type	Chassis Mount
	Size / Dimension	5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)
Report errors		Report errors?

#### **ABC550-1T15 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **ABC550-1T15 Payment Methods**





















### **ABC550-1T15 Shipping Methods**













If you have any question about ABC550-1T15, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com