



ABE03DHAS Information

Heisener.com

Part Number ABE03DHAS

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FEMALE 6POS 0.039

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ABE03DHAS Specifications

Manufacturer Part Number ABE03DHAS Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 3 Number of Positions 6 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.039" (1.00mm) Features - Mounting Type Through Hole, Right Angle Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Thickness 10µin (0.25µm) Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	71DE05D11715 Specifications	
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 3 Number of Positions 6 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.039" (1.00mm) Features - Mounting Type Through Hole, Right Angle Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Manufacturer Part Number	ABE03DHAS
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row3Number of Positions6Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 3 Number of Positions 6 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.039" (1.00mm) Features - Mounting Type Through Hole, Right Angle Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 3 Number of Positions 6 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.039" (1.00mm) Features - Mounting Type Through Hole, Right Angle Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row3Number of Positions6Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Package	-
Gender Female Number of Positions/Bay/Row 3 Number of Positions 6 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.039" (1.00mm) Features - Mounting Type Through Hole, Right Angle Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Series	-
Number of Positions/Bay/Row3Number of Positions6Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions6Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	3
Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions	6
Pitch0.039" (1.00mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
Features Mounting Type Through Hole, Right Angle Termination Solder, Staggered Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 10μin (0.25μm) Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Number of Rows	2
Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature -65 °C ~ 150 °C	Pitch	0.039" (1.00mm)
Termination Solder, Staggered Solder, Staggered Solder, Staggered Solder, Staggered Solder, Staggered Solder Sold	Features	-
Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, $0.125''$ ($3.18mm$) Dia Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Mounting Type	Through Hole, Right Angle
Contact Finish Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Termination	Solder, Staggered
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Hairpin Bellows Color - Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Material	Beryllium Copper
Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Contact Finish	Gold
Color - Side Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature - 65 °C ~ 150 °C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Side Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature -65 °C ~ 150 °C	Contact Type	Hairpin Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	-
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

ABE03DHAS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ABE03DHAS Payment Methods





















ABE03DHAS Shipping Methods













If you have any question about ABE03DHAS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com