



### **ABE20DHAS Information**

Heisener.com

Part Number ABE20DHAS

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 40POS 0.039

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **ABE20DHAS Specifications**

| Manufacturer Part Number         ABE20DHAS           Manufacturer         Sullins Connector Solutions           Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         20           Number of Positions         40           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.039" (1.00mm)           Features         -           Mounting Type         Through Hole, Right Angle           Termination         Solder, Staggered           Contact Material         Beryllium Copper           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Hairpin Bellows           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C  | ADD20DIMS Specifications    |   |
|---|-----------------------------|---|
| Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         20           Number of Positions         40           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.039" (1.00mm)           Features         -           Mounting Type         Through Hole, Right Angle           Termination         Solder, Staggered           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Type         Hairpin Bellows           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C  | Manufacturer Part Number    | ABE20DHAS   |
| Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C  | Manufacturer                | Sullins Connector Solutions                         |
| Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         20           Number of Positions         40           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.039" (1.00mm)           Features         -           Mounting Type         Through Hole, Right Angle           Termination         Solder, Staggered           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Hairpin Bellows           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C   | Category                    | Connectors, Interconnects                           |
| Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         20           Number of Positions         40           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.039" (1.00mm)           Features         -           Mounting Type         Through Hole, Right Angle           Termination         Solder, Staggered           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Hairpin Bellows           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C   |                             | Card Edge Connectors - Edgeboard Connectors         |
| Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C   | Package                     | -   |
| Gender         Female           Number of Positions/Bay/Row         20           Number of Positions         40           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.039" (1.00mm)           Features         -           Mounting Type         Through Hole, Right Angle           Termination         Solder, Staggered           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Hairpin Bellows           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C  | Series                      | -   |
| Number of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C   | Card Type                   | Non Specified - Dual Edge                           |
| Number of Positions  Card Thickness  0.062" (1.57mm)  Number of Rows  2  Pitch  0.039" (1.00mm)  Features  -  Mounting Type  Through Hole, Right Angle  Termination  Solder, Staggered  Contact Material  Beryllium Copper  Contact Finish  Gold  Contact Finish Thickness  10µin (0.25µm)  Contact Type  Hairpin Bellows  Color  Flange Feature  Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -65°C ~ 150°C   | Gender                      | Female  |
| Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C   | Number of Positions/Bay/Row | 20  |
| Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C  | Number of Positions         | 40  |
| Pitch0.039" (1.00mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C   | Card Thickness              | 0.062" (1.57mm)                                     |
| Features  Mounting Type Through Hole, Right Angle  Termination Solder, Staggered  Contact Material Beryllium Copper  Contact Finish Contact Finish Thickness 10μin (0.25μm)  Contact Type Hairpin Bellows  Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -65°C ~ 150°C   | Number of Rows              | 2   |
| Mounting TypeThrough Hole, Right AngleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature $-65$ °C ~ $150$ °C   | Pitch                       | 0.039" (1.00mm)                                     |
| Termination Solder, Staggered Solder, Staggered Solder, Staggered Solder, Staggered Solder, Staggered Solder Sold | Features                    | -   |
| Contact Material Beryllium Copper  Contact Finish Gold  Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Hairpin Bellows  Color -  Flange Feature Side Mount Opening, Unthreaded, $0.125''$ ( $3.18mm$ ) Dia  Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$  | Mounting Type               | Through Hole, Right Angle                           |
| Contact Finish Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, $0.125"$ ( $3.18mm$ ) Dia Operating Temperature $-65^{\circ}C \sim 150^{\circ}C$   | Termination                 | Solder, Staggered                                   |
| Contact Finish Thickness $10\mu in (0.25\mu m)$<br>Contact Type Hairpin Bellows<br>Color - Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia<br>Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$  | Contact Material            | Beryllium Copper                                    |
| Contact Type Hairpin Bellows  Color -  Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 150°C  | Contact Finish              | Gold  |
| Color - Side Mount Opening, Unthreaded, $0.125$ " ( $3.18$ mm) Dia Operating Temperature - $65$ °C ~ $150$ °C   | Contact Finish Thickness    | 10μin (0.25μm)                                      |
| Flange Feature Side Mount Opening, Unthreaded, $0.125$ " ( $3.18$ mm) Dia Operating Temperature $-65$ °C $\sim 150$ °C  | Contact Type                | Hairpin Bellows                                     |
| Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$  | Color                       | -   |
|   | Flange Feature              | Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia |
| Report errors?  | Operating Temperature       | -65°C ~ 150°C                                       |
|   |                             | Report errors?                                      |

#### **ABE20DHAS Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **ABE20DHAS Payment Methods**



















### **ABE20DHAS Shipping Methods**













If you have any question about ABE20DHAS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com