

ABE20DHHN

ABE20DHHN Information

Heisener.com	 ABE20DHHN Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 40POS 0.039 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ABE20DHHN Specifications

ManufacturerSullins Connector SolutionsCardegoryConnectors, Ledgeboard ConnectorsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.039" (1.00mm)Features-Numing Type0.039" (1.00mm)Contact FinishSolder, StaggeredContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairjin BellowsContact TypeBackFaquere Feature10µin (0.25µm)	-	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough HoleContact MaterialSolder, StaggeredContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsContact TypeBackFaquere-Contact TypeSlackFaquere-ColorBackFaquere-Coperating Temperature-65°C ~ 150°C	Manufacturer Part Number	ABE20DHHN
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough HoleContact MaterialSolder, StaggeredContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsContact TypeBackFlange Feature-Operating Temperature-65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough HoleContact MaterialSolder, StaggeredContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsContact TypeBackFlange Feature-Operating Temperature-65°C ~ 150°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough HoleContact FinishSolder, StaggeredContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C~150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough HoleContact FinishSolder, StaggeredContact Finish ThicknessGoldContact TypeHairpin BellowsContact TypeBeryllium CopperContact TypeGoldContact TypeHairpin BellowsColorBlackFaureg Feature-Operating Temperature-65°C ~ 150°C	Package	-
GenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough HoleContact MaterialSolder, StaggeredContact FinishGoldContact TypeIoµin (0.25µm)Contact TypeBackFlange Feature-Operating Temperatureo.5°C ~ 150°C	Series	-
Number of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough HoleContact MaterialSolder, StaggeredContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBiackFlange Feature-Operating Temperature65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions 40 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.039" (1.00mm) Features - Mounting Type Through Hole Contact Material Solder, Staggered Contact Finish Gold Contact Finish Thickness Ioµin (0.25µm) Contact Type Hairpin Bellows Color Black Flange Feature - Operating Temperature -	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	20
Number of Rows2Pitch0.039" (1.00mm)Features-Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions	40
Pitch0.039" (1.00mm)Features-Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)ColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish ThicknessIoµin (0.25µm)Contact TypeBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Pitch	0.039" (1.00mm)
TerminationSolder, StaggeredContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Termination	Solder, Staggered
Contact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Contact Material	Beryllium Copper
Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Contact Finish	Gold
ColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Contact Finish Thickness	10µin (0.25µm)
Flange Feature-Operating Temperature-65°C ~ 150°C	Contact Type	Hairpin Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

ABE20DHHN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ABE20DHHN Payment Methods



ABE20DHHN Shipping Methods



If you have any question about ABE20DHHN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com