



ABM08DRSH Information

Heisener.com

Part Number ABM08DRSH

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 16POS 0.156

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ABM08DRSH Specifications

| Manufacturer Part Number ABM08DRSH Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 8 Number of Positions 16 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Thickness 10µin (0.25µm) Contact Type Loop Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C | ABMOODRSH Specifications | | |
|---|-----------------------------|--|------|
| Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 8 Number of Positions 16 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Loop Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C | Manufacturer Part Number | ABM08DRSH | |
| Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C | Manufacturer | Sullins Connector Solutions | |
| Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 8 Number of Positions 16 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Loop Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C | Category | Connectors, Interconnects | |
| Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C | | Card Edge Connectors - Edgeboard Connectors | |
| Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C | Package | - | |
| GenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C | Series | - | |
| Number of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C | Card Type | Non Specified - Dual Edge | |
| Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C | Gender | Female | |
| Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C | Number of Positions/Bay/Row | 8 | |
| Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C | Number of Positions | 16 | |
| Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C | Card Thickness | 0.062" (1.57mm) | |
| Features Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 10μin (0.25μm) Contact Type Loop Bellows Color Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C | Number of Rows | 2 | |
| Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness 10μ in $(0.25\mu$ m)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125 " $(3.18$ mm) DiaOperating Temperature -65 °C ~ 150 °C | Pitch | 0.156" (3.96mm) | |
| Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Loop Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, $0.125''$ ($3.18mm$) Dia Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$ | Features | - | |
| Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness 10μ in $(0.25\mu$ m)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125 " $(3.18$ mm) DiaOperating Temperature -65 °C ~ 150 °C | Mounting Type | Through Hole | |
| Contact Finish Contact Finish Thickness 10μ in $(0.25\mu$ m) Contact Type Loop Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125 " $(3.18$ mm) Dia Operating Temperature -65 °C ~ 150 °C | Termination | Solder | |
| Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Loop Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$ | Contact Material | Beryllium Copper | |
| Contact Type Loop Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature -65 °C ~ 150 °C | Contact Finish | Gold | |
| Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature -65 °C ~ 150 °C | Contact Finish Thickness | 10μin (0.25μm) | |
| Flange Feature Top Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature -65 °C ~ 150 °C | Contact Type | Loop Bellows | |
| Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$ | Color | Green | |
| | Flange Feature | Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia | |
| Report errors? | Operating Temperature | -65°C ~ 150°C | |
| | | Report error | ors? |

ABM08DRSH Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ABM08DRSH Payment Methods



















ABM08DRSH Shipping Methods













If you have any question about ABM08DRSH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com