



ABM12DTKS Information

Heisener.com

Part Number ABM12DTKS

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 24POS 0.156

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ABM12DTKS Specifications

Manufacturer Part Number ABM12DTKS Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 12 Number of Positions 24 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Loop Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	•	
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 12 Number of Positions 24 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Type Loop Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Manufacturer Part Number	ABM12DTKS
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 12 Number of Positions 24 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Type Loop Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 12 Number of Positions 24 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Loop Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 12 Number of Positions 24 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Loop Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Package	-
Gender Female Number of Positions/Bay/Row 12 Number of Positions 24 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Loop Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Series	-
Number of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions 24 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Loop Bellows Color Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	12
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions	24
Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
Features Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 10μin (0.25μm) Contact Type Loop Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Pitch	0.156" (3.96mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature -65 °C ~ 150°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, $0.125"$ ($3.18mm$) DiaOperating Temperature $-65^{\circ}C \sim 150^{\circ}C$	Mounting Type	Through Hole
Contact Finish Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Loop Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Termination	Solder
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Loop Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Material	Beryllium Copper
Contact Type Loop Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Contact Finish	Gold
Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Side Mount Opening, Unthreaded, 0.125 " (3.18mm) Dia Operating Temperature -65 °C ~ 150 °C	Contact Type	Loop Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Green
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

ABM12DTKS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ABM12DTKS Payment Methods



















ABM12DTKS Shipping Methods













If you have any question about ABM12DTKS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com