



ABM28DSEF Information

Heisener.com

Part Number ABM28DSEF

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 56POS 0.156

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ABM28DSEF	Specifications
ADMIZOUSET	Specifications

Manufacturer Part Number ABM28DSEF Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 28 Number of Positions 56 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	ADM20D5D1 Specifications	
Category Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 28 Number of Positions 56 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Manufacturer Part Number	ABM28DSEF
Card Edge Connectors - Edgeboard Connectors Package Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 28 Number of Positions 56 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 28 Number of Positions 56 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions / Bay/Row 28 Number of Positions 56 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia		Card Edge Connectors - Edgeboard Connectors
Card Type	Package	-
GenderFemaleNumber of Positions/Bay/Row28Number of Positions56Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Series	-
Number of Positions/Bay/Row 28 Number of Positions 56 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Card Type	Non Specified - Dual Edge
Number of Positions 56 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Number of Positions/Bay/Row	28
Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Number of Positions	56
Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Card Thickness	0.062" (1.57mm)
Features Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Number of Rows	2
Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Pitch	0.156" (3.96mm)
Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Features	-
Contact Material Contact Finish Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Beryllium Copper Gold Contact Type Full Bellows Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Mounting Type	Panel Mount
Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Termination	Solder Eyelet(s)
Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Contact Material	Beryllium Copper
Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Contact Finish	Gold
Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Contact Type	Full Bellows
	Color	Green
	Flange Feature	Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Operating Temperature	-65°C ~ 150°C
Report errors		Report errors?

ABM28DSEF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ABM28DSEF Payment Methods



















ABM28DSEF Shipping Methods













If you have any question about ABM28DSEF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com