

AC4790-1X1 Information

Heisener.com

Part Number AC4790-1X1

Manufacturer Laird - Embedded Wireless Solutions

Category RF/IF and RFID

RF Transceiver Modules

Description 902 - 928 MHZ FHSS 0 - 10 MW

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AC4790-1X1 Specifications

Manufacturer Part Number AC4790-1X1 Manufacturer Laird - Embedded Wireless Solutions Category RF/IF and RFID RF Transceiver Modules RF Transceiver Modules Package - Series - RF Family/Standard - Protocol - Modulation FHSS, FSK Frequency 902MHz ~ 928MHz Data Rate - Power - Output 10dBm Sensitivity -99dBm Serial Interfaces - Antenna Type Not Included, Castellation Memory Size - Voltage - Supply 3.3V Current - Receiving - Current - Transmitting - Mounting Type Surface Mount Operating Temperature -40°C ~ 80°C Package / Case - In the processor of the		
Category RF/IF and RFID Ref Transceiver Modules Package - Series - RF Family/Standard - Protocol - Modulation FHSS, FSK Frequency 902MHz ~ 928MHz Data Rate - Power - Output 10dBm Sensitivity -99dBm Serial Interfaces - Antenna Type Not Included, Castellation Memory Size - Voltage - Supply 3.3V Current - Receiving - Current - Transmitting - Mounting Type Surface Mount Operating Temperature -40°C ~ 80°C Package / Case -	Manufacturer Part Number	AC4790-1X1
Package - Series - RF Family/Standard - Protocol - Modulation FHSS, FSK Frequency 902MHz ~ 928MHz Data Rate - Power - Output 10dBm Sensitivity -99dBm Serial Interfaces - Antenna Type Not Included, Castellation Memory Size - Voltage - Supply 3.3V Current - Receiving - Current - Transmitting - Mounting Type Surface Mount Operating Temperature -40°C ~ 80°C Package / Case -	Manufacturer	Laird - Embedded Wireless Solutions
Package - Series - RF Family/Standard - Protocol - Modulation FHSS, FSK Frequency 902MHz ~ 928MHz Data Rate - Power - Output 10dBm Sensitivity -99dBm Serial Interfaces - Antenna Type Not Included, Castellation Memory Size - Voltage - Supply 3.3V Current - Receiving - Current - Transmitting - Mounting Type Surface Mount Operating Temperature -40°C ~ 80°C Package / Case -	Category	RF/IF and RFID
Series - RF Family/Standard - Protocol - Modulation FHSS, FSK Frequency 902MHz ~ 928MHz Data Rate - Power - Output 10dBm Sensitivity -99dBm Serial Interfaces - Antenna Type Not Included, Castellation Memory Size - Voltage - Supply 3.3V Current - Receiving - Current - Transmitting - Mounting Type Surface Mount Operating Temperature -40°C ~ 80°C Package / Case -		RF Transceiver Modules
RF Family/Standard - Protocol - Modulation FHSS, FSK Frequency 902MHz ~ 928MHz Data Rate - Power - Output 10dBm Sensitivity -99dBm Serial Interfaces - Antenna Type Not Included, Castellation Memory Size - Voltage - Supply 3.3V Current - Receiving - Current - Transmitting - Mounting Type Surface Mount Operating Temperature -40°C ~ 80°C Package / Case -	Package	-
Protocol FHSS, FSK Frequency 902MHz ~ 928MHz Data Rate - Power - Output 10dBm Sensitivity -99dBm Serial Interfaces - Antenna Type Not Included, Castellation Memory Size - Voltage - Supply 3.3V Current - Receiving - Current - Transmitting - Mounting Type Surface Mount Operating Temperature -40°C ~ 80°C Package / Case -	Series	-
ModulationFHSS, FSKFrequency902MHz ~ 928MHzData Rate-Power - Output10dBmSensitivity-99dBmSerial Interfaces-Antenna TypeNot Included, CastellationMemory Size-Voltage - Supply3.3VCurrent - Receiving-Current - Transmitting-Mounting TypeSurface MountOperating Temperature-40°C ~ 80°CPackage / Case-	RF Family/Standard	-
Frequency Data Rate - Power - Output 10dBm Sensitivity -99dBm Serial Interfaces - Antenna Type Not Included, Castellation Memory Size - Voltage - Supply 3.3V Current - Receiving Current - Transmitting Mounting Type Surface Mount Operating Temperature -40°C ~ 80°C Package / Case -	Protocol	-
Data Rate Power - Output 10dBm Sensitivity -99dBm Serial Interfaces - Antenna Type Not Included, Castellation Memory Size - Voltage - Supply 3.3V Current - Receiving Current - Transmitting Mounting Type Surface Mount Operating Temperature Package / Case	Modulation	FHSS, FSK
Power - Output Sensitivity -99dBm Serial Interfaces - Antenna Type Not Included, Castellation Memory Size - Voltage - Supply 3.3V Current - Receiving - Current - Transmitting Mounting Type Surface Mount Operating Temperature -40°C ~ 80°C Package / Case - Indepty Control - Output -	Frequency	902MHz ~ 928MHz
Sensitivity -99dBm Serial Interfaces - Antenna Type Not Included, Castellation Memory Size - Voltage - Supply 3.3V Current - Receiving - Current - Transmitting - Mounting Type Surface Mount Operating Temperature -40°C ~ 80°C Package / Case -	Data Rate	-
Serial Interfaces Antenna Type Not Included, Castellation Memory Size - Voltage - Supply 3.3V Current - Receiving - Current - Transmitting Mounting Type Surface Mount Operating Temperature -40°C ~ 80°C Package / Case -	Power - Output	10dBm
Antenna Type Memory Size Voltage - Supply Current - Receiving Current - Transmitting Mounting Type Surface Mount Operating Temperature Package / Case Not Included, Castellation - Surface Mount - Surface Mount - - - - - - - - - - - - -	Sensitivity	-99dBm
Memory Size-Voltage - Supply3.3VCurrent - Receiving-Current - Transmitting-Mounting TypeSurface MountOperating Temperature-40°C ~ 80°CPackage / Case-	Serial Interfaces	-
Voltage - Supply Current - Receiving - Current - Transmitting Mounting Type Surface Mount Operating Temperature Package / Case - 3.3V - - - - - - - - - - - - -	Antenna Type	Not Included, Castellation
Current - Receiving Current - Transmitting Mounting Type Surface Mount Operating Temperature -40°C ~ 80°C Package / Case -	Memory Size	-
Current - Transmitting - Mounting Type Surface Mount Operating Temperature -40°C ~ 80°C Package / Case -	Voltage - Supply	3.3V
Mounting Type Surface Mount	Current - Receiving	-
Operating Temperature -40°C ~ 80°C Package / Case -	Current - Transmitting	-
Package / Case -	Mounting Type	Surface Mount
	Operating Temperature	-40°C ~ 80°C
Report errors?	Package / Case	-
		Report errors?

AC4790-1X1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AC4790-1X1 Payment Methods



















AC4790-1X1 Shipping Methods













If you have any question about AC4790-1X1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com