



ACB25DHND Information

Heisener.com

Part Number ACB25DHND

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 50POS 0.050

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ACB25DHND Specifications

Manufacturer Part Number ACB25DHND Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Type Hairpin Bellows Cotor Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Tiebzsbii ib speemeations		
Category Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Manufacturer Part Number	ACB25DHND	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Manufacturer	Sullins Connector Solutions	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Category	Connectors, Interconnects	
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Series	-	
Number of Positions/Bay/Row Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Hairpin Bellows Color Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Card Type	Non Specified - Dual Edge	
Number of Positions50Card Thickness $0.062"$ (1.57mm)Number of Rows2Pitch $0.050"$ (1.27mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $30μin (0.76μm)$ Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, $0.125"$ (3.18mm) DiaOperating Temperature $-65°C \sim 150°C$	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	25	
Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Number of Positions	50	
Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)	
Features Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 30μin (0.76μm) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Number of Rows	2	
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Pitch	0.050" (1.27mm)	
Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μ in $(0.76\mu$ m) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125 " $(3.18$ mm) Dia Operating Temperature -65 °C ~ 150 °C	Features	-	
Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μ in $(0.76\mu$ m) Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125 " $(3.18$ mm) Dia Operating Temperature -65 °C ~ 150 °C	Mounting Type	Through Hole	
Contact Finish Gold Contact Finish Thickness 30μ in $(0.76\mu m)$ Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125 " ($3.18mm$) Dia Operating Temperature -65 °C ~ 150 °C	Termination	Solder	
Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Material	Beryllium Copper	
Contact Type Hairpin Bellows Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Contact Finish	Gold	
Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125 " (3.18mm) Dia Operating Temperature -65 °C ~ 150 °C	Contact Finish Thickness	30μin (0.76μm)	
Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125 " (3.18mm) Dia Operating Temperature -65 °C ~ 150 °C	Contact Type	Hairpin Bellows	
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Black	
	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors	Operating Temperature	-65°C ~ 150°C	
Report circles:			Report errors?

ACB25DHND Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ACB25DHND Payment Methods



















ACB25DHND Shipping Methods













If you have any question about ACB25DHND, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com