

# **ACB60DHLN**

## **ACB60DHLN Information**

Heisener.com	 ACB60DHLN Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 120POS .050 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **ACB60DHLN Specifications**

ManufacturerSullins Connector SolutionsCardectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Stries-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row60Number of Positions120Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeNinogh HoleContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpi BellowsContact TypeBiackFaquere FeatureSolderContact TypeSolderContact TypeSold	-	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row60Number of Positions120Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsContact TypeBlackFauge Feature-Coperating Temperature-65°C ~ 150°C	Manufacturer Part Number	ACB60DHLN
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row60Number of Positions120Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsContact Type19µin BellowsContact Type19µin BellowsColorBlackFinage Feature-Operating Temperature-65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row60Number of Positions120Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsContact TypeSolderContact Type50/cSolder50/cContact Type50/cColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row60Number of Positions120Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleContact Finish ThicknessSolderContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row60Number of Positions120Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessJuin (0.76µm)Contact TypeHaripin BellowsColorBlackFlange Feature-Operating Temperature65°C ~ 150°C	Package	-
GenderFemaleNumber of Positions/Bay/Row60Number of Positions120Card Thickness0.662°(1.57mm)Number of Rows2Pitch0.50°(1.27mm)Features-Mounting TypeMong HoleContact MaterialSolderContact FinishGoldContact Finish ThicknessGoldContact TypeHairpi BellowsContact TypeBiakFlange Feature-Coperating Temperature65°C~150°C	Series	-
Number of Positions/Bay/Row60Number of Positions120Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions120Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	60
Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions	120
Pitch0.050" (1.27mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)ColorBlackFlange Feature-Operating Temperature65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperatures-55°C ~ 150°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Pitch	0.050" (1.27mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Contact Material	Beryllium Copper
Contact TypeHairpin BellowsColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Contact Finish	Gold
ColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Contact Finish Thickness	30µin (0.76µm)
Flange Feature-Operating Temperature-65°C ~ 150°C	Contact Type	Hairpin Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

### **ACB60DHLN Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ACB60DHLN Payment Methods**



### **ACB60DHLN Shipping Methods**



If you have any question about ACB60DHLN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com