

ACB90DYFN

ACB90DYFN Information

Contraction the	Part Number Manufacturer Category Description Package	ACB90DYFN Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 180POS .050 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ACB90DYFN Specifications

ManufacturerSullins Connector SolutionsCardecors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Series-Card TypeMon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row90Number of Positions180Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.050° (1.27mm)Features-Mounting TypeSulface MountContact MaterialSolderContact FinishGoldContact Finish Thickness3µin (0.76µm)Contact TypeCantileverContact TypeGuin (0.76µm)Contact Finish Thickness3µin (0.76µm)Contact Finish ThicknessSulface MountContact TypeGuin (2.6µm)Contact Finish ThicknessSulface MountContact TypeGuin (2.6µm)Contact Finish ThicknessSulface MountContact Finish ThicknessSulface MountContact TypeGuin (2.6µm)Contact TypeCantileverContact Finish ThicknessSulface MountContact Finish ThicknessSulface MountContact TypeCantileverContact TypeCantileverContact TypeCantileverContact TypeSulfaceContact TypeCantileverContact TypeCantileverContact TypeCantileverContact TypeCantileverContact Type <td< th=""><th></th><th></th></td<>		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row90Number of Positions180Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeBlackFlange Feature-ColorBlackFlange Feature-Operating Temperature65°C ~ 150°C	Manufacturer Part Number	ACB90DYFN
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row90Number of Positions180Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSulface MountContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeCantileverContact TypeSulfaceMountContact Finish ThicknessGoldContact TypeEalekerColorBlackFlange Feature-Operating Temperature65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row90Number of Positions180Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeSurfaceMountContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderColorBlackFlange Feature-Operating Temperature-5°C~150°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row90Number of Positions/Bay/Row180Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountContact Finish ThicknessSolderContact Finish Thickness30µin (0.76µm)Contact TypeGuidContact TypeSufarce MountContact Finish ThicknessBeryllium CopperContact TypeSupin (0.76µm)Contact TypeSupin (0.76µm)ColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row90Number of Positions180Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountContact MaterialSolderContact Finish ThicknessGoldContact TypeGupin (0.76µm)Contact TypeGupin (0.76µm)Contact TypeBackFage Feature-Operating Temperature65°C ~ 150°C	Package	-
GenderFemaleNumber of Positions/Bay/Row90Number of Positions180Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact MaterialBeryllium CopperContact Finish Thickness30µin (0.76µm)Contact TypeGantileverColorBlackFlange Feature-Operating Temperature-Solor C 150°C-	Series	-
Number of Positions/Bay/Row90Number of Positions180Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions 180 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.050" (1.27mm) Features - Mounting Type Surface Mount Termination Solder Contact Material Beryllium Copper Contact Finish Thickness Gold Contact Type Cantilever Color Black Flange Feature - Operating Temperature -	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	90
Number of Rows2Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions	180
Pitch0.050" (1.27mm)Features-Mounting TypeSurface MountTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)ColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeSurface MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-50°C ~ 150°C	Number of Rows	2
Mounting TypeSurface MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 150°C	Pitch	0.050" (1.27mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Mounting Type	Surface Mount
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Contact Material	Beryllium Copper
Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-65°C ~ 150°C	Contact Finish	Gold
Color Black Flange Feature - Operating Temperature -65°C ~ 150°C	Contact Finish Thickness	30µin (0.76µm)
Flange Feature-Operating Temperature-65°C ~ 150°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}C \sim 150^{\circ}C$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	$-65^{\circ}C \sim 150^{\circ}C$
		Report errors?

ACB90DYFN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ACB90DYFN Payment Methods





If you have any question about ACB90DYFN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com