



## ACC02E-36-11S(G96) Information

Heisener.com

ACC02E-36-11S(G96) Part Number

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

CONN RCPT 48POS BOX MNT W/SCKT **Description** 

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## ACC02E-36-11S(G96) Specifications

Manufacturer Part Number       ACC02E-36-11S(G96)         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Package       -         Series       AC, MIL-5015 Derivative         Connector Type       Receptacle, Female Sockets         Number of Positions       48         Shell Size - Insert       36-11         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Crimp         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Anodic Coating (Alumilite)         Contact Finish       Silver         Features       -         Voltage - Rated       500VAC, 700VDC         Current Rating       -         Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesAC, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions48Shell Size - Insert36-11Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer Part Number	ACC02E-36-11S(G96)
Package-SeriesAC, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions48Shell Size - Insert36-11Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesAC, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions48Shell Size - Insert36-11Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Category	Connectors, Interconnects
SeriesAC, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions48Shell Size - Insert36-11Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions48Shell Size - Insert36-11Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions  Shell Size - Insert  36-11  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Anodic Coating (Alumilite)  Contact Finish  Features  -  Voltage - Rated  500VAC, 700VDC  Current Rating  -	Series	AC, MIL-5015 Derivative
Shell Size - Insert36-11Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange  Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite)  Contact Finish Features - Voltage - Rated SouvAC, 700VDC  Current Rating -	Number of Positions	48
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size - Insert	36-11
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Anodic Coating (Alumilite)  Contact Finish  Features  -  Voltage - Rated  500VAC, 700VDC  Current Rating  -	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Crimp
Ingress Protection  Environment Resistant  Aluminum, Anodic Coating (Alumilite)  Contact Finish  Silver  Features  - Voltage - Rated  Current Rating  Environment Resistant  Aluminum, Anodic Coating (Alumilite)  Silver  -  -  -  -  -  -  -  -  -  -  -  -  -	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  - Voltage - Rated  Current Rating  Aluminum, Anodic Coating (Alumilite)  Silver  - Current Rating	Orientation	N (Normal)
Contact Finish Silver  Features - Voltage - Rated Current Rating - Silver -	Ingress Protection	Environment Resistant
Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 500VAC, 700VDC  Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
•	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

## ACC02E-36-11S(G96) Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## ACC02E-36-11S(G96) Payment Methods



















## ACC02E-36-11S(G96) Shipping Methods













If you have any question about ACC02E-36-11S(G96), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com