

### ACC06E-24-67S(025) Information

Heisener.com

ACC06E-24-67S(025) Part Number

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects **Circular Connectors** 

**Description** CONN PLUG 19POS INLINE SKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## ACC06E-24-67S(025) Specifications

Manufacturer Part Number  ACC06E-24-67S(025)  Manufacturer  Amphenol Industrial Operations  Category  Connectors, Interconnects  Circular Connectors  Package  - Series  AC, MIL-5015 Derivative  Connector Type  Plug, Female Sockets  Number of Positions  19  Shell Size - Insert  24-67  Shell Size, MIL  - Mounting Type  Free Hanging (In-Line)  Termination  Crimp  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Black Zinc Cobalt Plated  Contact Finish  Features  Mounting Hardware, Strain Relief  Voltage - Rated  Current Rating  -  Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesAC, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions19Shell Size - Insert24-67Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesMounting Hardware, Strain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Manufacturer Part Number	ACC06E-24-67S(025)
Package-SeriesAC, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions19Shell Size - Insert24-67Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesMounting Hardware, Strain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package - Series AC, MIL-5015 Derivative Connector Type Plug, Female Sockets Number of Positions 19 Shell Size - Insert 24-67 Shell Size, MIL - Crimp Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated Current Rating - Connected Sockets AC, MIL-5015 Derivative AC, MIL-5	Category	Connectors, Interconnects
Series AC, MIL-5015 Derivative  Connector Type Plug, Female Sockets  Number of Positions 19  Shell Size - Insert 24-67  Shell Size, MIL		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions19Shell Size - Insert24-67Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesMounting Hardware, Strain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Package	-
Number of Positions  Shell Size - Insert  24-67  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Crimp  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Black Zinc Cobalt Plated  Contact Finish  Features  Mounting Hardware, Strain Relief  Voltage - Rated  Courrent Rating  -	Series	AC, MIL-5015 Derivative
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Features Mounting Hardware, Strain Relief Voltage - Rated Current Rating -	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Threaded Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated  Contact Finish Features Mounting Hardware, Strain Relief  Voltage - Rated Current Rating	Number of Positions	19
Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Black Zinc Cobalt Plated  Contact Finish Silver  Features Mounting Hardware, Strain Relief  Voltage - Rated 200VAC, 250VDC  Current Rating -	Shell Size - Insert	24-67
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Black Zinc Cobalt Plated  Contact Finish  Silver  Features  Mounting Hardware, Strain Relief  Voltage - Rated  200VAC, 250VDC  Current Rating  -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Mounting Hardware, Strain Relief  Voltage - Rated  Current Rating  Aluminum, Black Zinc Cobalt Plated  Silver  Mounting Hardware, Strain Relief	Orientation	N (Normal)
Contact Finish  Features  Mounting Hardware, Strain Relief  Voltage - Rated  200VAC, 250VDC  Current Rating  -	Ingress Protection	Environment Resistant
Features Mounting Hardware, Strain Relief  Voltage - Rated 200VAC, 250VDC  Current Rating -	Shell Material, Finish	Aluminum, Black Zinc Cobalt Plated
Voltage - Rated 200VAC, 250VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	Mounting Hardware, Strain Relief
	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	-
		Report errors?

## ACC06E-24-67S(025) Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## ACC06E-24-67S(025) Payment Methods



















## ACC06E-24-67S(025) Shipping Methods













If you have any question about ACC06E-24-67S(025), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com