

### ACC08E-32-5S(003) Information

Heisener.com

Part Number ACC08E-32-5S(003)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 2POS RT ANG W/SCKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# ACC08E-32-5S(003) Specifications

Manufacturer Part Number     ACC08E-32-5S(003)       Manufacturer     Amphenol Industrial Operations       Category     Connectors, Interconnects       Circular Connectors       Package     -       Series     AC, MIL-5015 Derivative       Connector Type     Plug, Female Sockets       Number of Positions     2       Shell Size - Insert     32-5       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line), Right Angle       Termination     Crimp       Fastening Type     Threaded       Orientation     N (Normal)       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Olive Drab Cadmium Plated       Contact Finish     Silver       Features     Strain Relief       Voltage - Rated     900VAC, 1250VDC       Current Rating     -		
CategoryConnectors, InterconnectsPackage-SeriesAC, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert32-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer Part Number	ACC08E-32-5S(003)
Package-SeriesAC, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert32-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesAC, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert32-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Category	Connectors, Interconnects
Series AC, MIL-5015 Derivative Connector Type Plug, Female Sockets Number of Positions 2 Shell Size - Insert 32-5 Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert32-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Package	-
Number of Positions2Shell Size - Insert32-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Series	AC, MIL-5015 Derivative
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line), Right Angle  Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Features Strain Relief  Voltage - Rated 900VAC, 1250VDC  Current Rating  -	Number of Positions	2
Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Shell Size - Insert	32-5
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -	Termination	Crimp
Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 900VAC, 1250VDC  Current Rating -	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  900VAC, 1250VDC  Current Rating  -	Orientation	N (Normal)
Contact Finish  Features  Strain Relief  Voltage - Rated  900VAC, 1250VDC  Current Rating  -	Ingress Protection	Environment Resistant
Features Strain Relief  Voltage - Rated 900VAC, 1250VDC  Current Rating -	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 900VAC, 1250VDC  Current Rating -	Contact Finish	Silver
Current Rating -	Features	Strain Relief
	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	-
		Report errors?

### ACC08E-32-5S(003) Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### ACC08E-32-5S(003) Payment Methods



















## ACC08E-32-5S(003) Shipping Methods













If you have any question about ACC08E-32-5S(003), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com