

ACC10DEYN

ACC10DEYN Information

Contraction Com	Part Number Manufacturer Category Description Package	ACC10DEYN Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 20POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ACC10DEYN Specifications

Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish ThicknessSupin (0.76µm)Contact TypeCantileverColorSupin (0.76µm)ColorSupin (0.76µm)ColorSupin (0.76µm)ColorCantilever <tr< th=""><th></th><th></th></tr<>		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Nong HoleSolderContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness3ujn (0.76µm)Contact TypeCantileverContact TypeCantileverContact TypeSolderContact TypeSolderContact TypeCantileverContact TypeCantileverContact TypeSolderContact TypeCantileverColor-Fauge Feature-Operating Temperature65°C ~ 150°C	Manufacturer Part Number	ACC10DEYN
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions0062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeOlderContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeCantileverContact TypeCantileverContact Type-Fange Feature-Pinge Feature-Operating Temperature-Operating Temperature-50°C 150°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeSolderContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact Type-Contact TypeSoldieverContact TypeSoldieverContact Type-Fange Feature-Operating Temperature-Solder <t< td=""><td>Category</td><td>Connectors, Interconnects</td></t<>	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions/Bay/Row20Card Thickness0.062" (1.57mm)Number of Rows2Pich0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeGoldContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderContact TypeSolderColor-Fange Feature-Operating TemperatureSol ² < 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessGoldContact Type-Contact Type-Flange Feature-Color-Flange Feature-Operating Temperature-Solder-Solder-Color-Color-Color-Solder-Color-Color-Color-Color-Solder-Solder-Color-Color-Solder<	Package	-
GenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type0.100" (2.54mm)TerminationSolderContact MaterialBeryllium CopperContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange Feature-Pinge Feature-Operating Temperature-Solor Cantaf Scieler-Color-Solor-	Series	-
Number of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions 20 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type - Mounting Type Solder Contact Material Solder Contact Finish Gold Contact Finish Thickness Gold Contact Type Cantilever Color - Flange Feature - Operating Temperature -	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeCantileverColor-Flange Feature-Operating Temperature65°C ~ 150°C	Number of Positions/Bay/Row	10
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 150°C	Number of Positions	20
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeJupin (0.76µm)Color-Flange Feature-Operating Temperature65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish ThicknessSupin (0.76µm)Contact TypeCantileverColor-Flange Feature-Operating Temperatures-50°C ~ 150°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-55°C ~ 150°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature65°C ~ 150°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature65°C ~ 150°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature65°C ~ 150°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 150°C	Contact Material	Beryllium Copper
Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 150°C	Contact Finish	Gold
Color-Flange Feature-Operating Temperature-65°C ~ 150°C	Contact Finish Thickness	30µin (0.76µm)
Flange Feature-Operating Temperature-65°C ~ 150°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	-
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

ACC10DEYN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ACC10DEYN Payment Methods



ACC10DEYN Shipping Methods



If you have any question about ACC10DEYN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com