



### **ACC18DREF Information**

Heisener.com

Part Number ACC18DREF

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 36POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **ACC18DREF Specifications**

Manufacturer Part Number       ACC18DREF         Manufacturer       Sullins Connector Solutions         Category       Connectors, Interconnects         Package       -         Series       -         Card Type       Non Specified - Dual Edge         Gender       Female         Number of Positions/Bay/Row       18         Number of Positions       36         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.100" (2.54mm)         Features       -         Mounting Type       Panel Mount         Termination       Solder Eyelet(s)         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Type       Full Bellows         Color       Green         Flange Feature       Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia         Operating Temperature       -65°C ~ 150°C	ACCIODALLI Specifications	
Category Card Edge Connectors - Edgeboard Connectors  Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 18 Number of Positions 36 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Green Flange Feature To Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Manufacturer Part Number	ACC18DREF
Card Edge Connectors - Edgeboard Connectors  Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 18 Number of Positions 36 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 18 Number of Positions 36 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 18 Number of Positions 36 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia		Card Edge Connectors - Edgeboard Connectors
Card Type	Package	-
GenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Series	-
Number of Positions       18         Number of Positions       36         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.100" (2.54mm)         Features       -         Mounting Type       Panel Mount         Termination       Solder Eyelet(s)         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       30μin (0.76μm)         Contact Type       Full Bellows         Color       Green         Flange Feature       Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Card Type	Non Specified - Dual Edge
Number of Positions       36         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.100" (2.54mm)         Features       -         Mounting Type       Panel Mount         Termination       Solder Eyelet(s)         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       30μin (0.76μm)         Contact Type       Full Bellows         Color       Green         Flange Feature       Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Gender	Female
Card Thickness 0.062" (1.57mm)  Number of Rows 2  Pitch 0.100" (2.54mm)  Features	Number of Positions/Bay/Row	18
Number of Rows       2         Pitch       0.100" (2.54mm)         Features       -         Mounting Type       Panel Mount         Termination       Solder Eyelet(s)         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       30μin (0.76μm)         Contact Type       Full Bellows         Color       Green         Flange Feature       Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Number of Positions	36
Pitch       0.100" (2.54mm)         Features       -         Mounting Type       Panel Mount         Termination       Solder Eyelet(s)         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       30μin (0.76μm)         Contact Type       Full Bellows         Color       Green         Flange Feature       Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Card Thickness	0.062" (1.57mm)
Features  Mounting Type Panel Mount  Termination Solder Eyelet(s)  Contact Material Beryllium Copper  Contact Finish Gold Contact Finish Thickness 30μin (0.76μm)  Contact Type Full Bellows  Color Green  Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Number of Rows	2
Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Pitch	0.100" (2.54mm)
Termination Solder Eyelet(s)  Contact Material Beryllium Copper  Contact Finish Gold  Contact Finish Thickness 30μin (0.76μm)  Contact Type Full Bellows  Color Green  Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Features	-
Contact Material  Contact Finish  Contact Finish Thickness  30µin (0.76µm)  Contact Type  Full Bellows  Color  Green  Flange Feature  Beryllium Copper  Gold  Contact Finish Thickness  30µin (0.76µm)  Full Bellows  Color  Green  Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Mounting Type	Panel Mount
Contact Finish       Gold         Contact Finish Thickness       30μin (0.76μm)         Contact Type       Full Bellows         Color       Green         Flange Feature       Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Termination	Solder Eyelet(s)
Contact Finish Thickness 30μin (0.76μm)  Contact Type Full Bellows  Color Green  Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Contact Material	Beryllium Copper
Contact Type Full Bellows  Color Green  Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Contact Finish	Gold
Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Contact Finish Thickness	30μin (0.76μm)
Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Contact Type	Full Bellows
	Color	Green
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Flange Feature	Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia
	Operating Temperature	-65°C ~ 150°C
Report errors'		Report errors?

#### **ACC18DREF Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **ACC18DREF Payment Methods**



















### **ACC18DREF Shipping Methods**













If you have any question about ACC18DREF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com