



### **ACC24DTKH Information**

Heisener.com

Part Number ACC24DTKH

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 48POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **ACC24DTKH Specifications**

Manufacturer Part Number         ACC24DTKH           Manufacturer         Sullins Connector Solutions           Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         24           Number of Positions         48           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Contact Material         Beryllium Copper           Contact Finish Thickness         30µin (0.76µm)           Contact Type         Loop Bellows           Color         -           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C	71CC24D 1 Kill Specifications	
Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         24           Number of Positions         48           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Type         Loop Bellows           Color         -           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C	Manufacturer Part Number	ACC24DTKH
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         24           Number of Positions         48           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         30μin (0.76μm)           Contact Type         Loop Bellows           Color         -           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C	Category	Connectors, Interconnects
Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         24           Number of Positions         48           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         30μin (0.76μm)           Contact Type         Loop Bellows           Color         -           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Package	-
GenderFemaleNumber of Positions/Bay/Row24Number of Positions48Card Thickness $0.062" (1.57 mm)$ Number of Rows2Pitch $0.100" (2.54 mm)$ Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $30 \mu in (0.76 \mu m)$ Contact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, $0.125" (3.18 mm)$ DiaOperating Temperature $-65°C \sim 150°C$	Series	-
Number of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	24
Number of Rows2Pitch $0.100"$ (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $30\mu$ in (0.76 $\mu$ m)Contact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature $-65$ °C ~ $150$ °C	Number of Positions	48
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
Features  Mounting Type Through Hole  Termination Solder  Contact Material Beryllium Copper  Contact Finish Contact Finish Thickness 30μin (0.76μm)  Contact Type Loop Bellows  Color - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 150°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $30\mu in (0.76\mu m)$ Contact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature $-65^{\circ}$ C ~ $150^{\circ}$ C	Pitch	0.100" (2.54mm)
Termination Solder  Contact Material Beryllium Copper  Contact Finish Gold  Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Loop Bellows  Color -  Flange Feature Top Mount Opening, Unthreaded, $0.125$ " ( $3.18mm$ ) Dia  Operating Temperature $-65$ °C ~ $150$ °C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $30\mu$ in $(0.76\mu$ m)Contact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, $0.125$ " $(3.18$ mm) DiaOperating Temperature $-65$ °C ~ $150$ °C	Mounting Type	Through Hole
Contact Finish Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Loop Bellows Color - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Termination	Solder
Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Loop Bellows Color - Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Material	Beryllium Copper
Contact Type Loop Bellows  Color -  Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 150°C	Contact Finish	Gold
Color - Top Mount Opening, Unthreaded, $0.125$ " ( $3.18$ mm) Dia Operating Temperature $-65$ °C $\sim 150$ °C	Contact Finish Thickness	30μin (0.76μm)
Flange Feature Top Mount Opening, Unthreaded, $0.125$ " (3.18mm) Dia Operating Temperature $-65$ °C $\sim 150$ °C	Contact Type	Loop Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

#### **ACC24DTKH Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **ACC24DTKH Payment Methods**



















## **ACC24DTKH Shipping Methods**













If you have any question about ACC24DTKH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com