

ACC25DRXH

ACC25DRXH Information

Manufac Category	Manufacturer Category Description	ACC25DRXH Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 50POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ACC25DRXH Specifications

Manufacturer Part Number ACC25DRXH Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Cated Edge Connectors - Edgeboard Connectors Cated Edge Connectors - Edgeboard Connectors Package - Stries - Card Fdge Connectors - Edgeboard Connectors Cated Edge Connectors - Edgeboard Connectors Stries - Card Type - Gender Non Specified - Dual Edge Mumber of Positions/Bay/Row S5 Number of Positions/Bay/Row 50 Card Thickness 0.062° (1.57mm) Number of Rows 2 Pich 0.100° (2.54mm) Young Hole - Young Ho			
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Features-Nongh HoleSolderContact MaterialSolderContact Finish ThicknessSolderContact Finish ThicknessSupin CopperContact TypeFull BellowsContact TypeSpeanceContact TypeSupin CopperContact TypeGoldContact TypeSupin CoppersContact TypeSupin CoppersContact TypeSupin CoppersContact TypeSupin CoppersContact TypeSupin CoppersColorGreenFauge FeatureSolor CoppersSupin Copering, Unthreaded, 0.125° (3.18mm) DiaCoperating Temperature-55°C ~ 150°C	Manufacturer Part Number	ACC25DRXH	
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type50Contact MaterialSolderContact FinishGoldContact Finish ThicknessGoldContact TypeFull BellowsContact TypeSolderContact TypeSolderContact TypeGoldContact TypeGoldContact TypeSolderContact TypeSolderContact TypeGoldonsContact TypeSolderContact TypeSolderCont	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type6olderContact MaterialSolderContact FinishGoldContact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeFull BellowsContact TypeFull BellowsContact TypeGoldContact TypeGoldowsContact TypeSoldersContact TypeSoldersContact TypeGoldowsContact TypeSoldersContact TypeSolders	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact Finish ThicknessGoldContact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessSupin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature65°C ~ 150°C	Series	-	
Number of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type-Mounting TypeSolderContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessSoljin (0.76µm)Contact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-Sol°C ~ 150°C-	Card Type	Non Specified - Dual Edge	
Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Number of Rows 0.100" (2.54mm) Features - Mounting Type Through Hole Young Addrenial Solder Contact Material Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Green Flange Feature - Operating Temperature -65°C ~ 150°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type-TerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeSulpellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 150°C	Number of Positions/Bay/Row	25	
Number of Rows2Number of Rows0.100" (2.54mm)Features-Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions	50	
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeSulpin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C~150°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish ThicknessJujin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature-65°C ~ 150°C	Number of Rows	2	
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Pitch	0.100" (2.54mm)	
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Features	-	
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Mounting Type	Through Hole	
Contact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Termination	Solder	
Contact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Contact Material	Beryllium Copper	
Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Contact Finish	Gold	
ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Contact Finish Thickness	30µin (0.76µm)	
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Contact Type	Full Bellows	
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Green	
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 150°C	
			Report errors?

ACC25DRXH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ACC25DRXH Payment Methods





If you have any question about ACC25DRXH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com