



ACC26DREF Information

Heisener.com

Part Number ACC26DREF

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 52POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ACC26DREF Specifications

Manufacturer Part Number ACC26DREF Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 26 Number of Positions 52 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 150°C	ACCZODICET Specifications		
Category Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 26 Number of Positions 52 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 150°C	Manufacturer Part Number	ACC26DREF	
Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 26 Number of Positions 52 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 150°C	Manufacturer	Sullins Connector Solutions	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 26 Number of Positions 52 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 150°C	Category	Connectors, Interconnects	
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 26 Number of Positions 52 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Gold Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors	
Card Type Gender Female Number of Positions/Bay/Row 26 Number of Positions 52 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 150°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Series	-	
Number of Positions/Bay/Row Number of Positions 52 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 150°C	Card Type	Non Specified - Dual Edge	
Number of Positions52Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	26	
Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 150°C	Number of Positions	52	
Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 150°C	Card Thickness	0.062" (1.57mm)	
Features Mounting Type Panel Mount Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 150°C	Number of Rows	2	
Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness 30μ in $(0.76\mu$ m)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116 " (2.95mm) DiaOperating Temperature -65 °C ~ 150 °C	Pitch	0.100" (2.54mm)	
Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 150°C	Features	-	
Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μ in $(0.76\mu m)$ Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116 " $(2.95mm)$ Dia Operating Temperature -65° C $\sim 150^{\circ}$ C	Mounting Type	Panel Mount	
Contact Finish Gold Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116 " (2.95mm) Dia Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Termination	Solder Eyelet(s)	
Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, $0.116''$ (2.95mm) Dia Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Material	Beryllium Copper	
Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 150°C	Contact Finish	Gold	
Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116 " (2.95mm) Dia Operating Temperature -65 °C ~ 150 °C	Contact Finish Thickness	30μin (0.76μm)	
Flange Feature Top Mount Opening, Floating Bobbin, 0.116 " (2.95mm) Dia Operating Temperature -65 °C ~ 150 °C	Contact Type	Full Bellows	
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Green	
	Flange Feature	Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	
Donort owners	Operating Temperature	-65°C ~ 150°C	
Report errors			Report errors?

ACC26DREF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ACC26DREF Payment Methods



















ACC26DREF Shipping Methods













If you have any question about ACC26DREF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com