



ACC43DPGS Information

Heisener.com

Part Number ACC43DPGS

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 86POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ACC43DPGS Specifications

Manufacturer Part Number ACC43DPGS Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 43 Number of Positions 86 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Thickness 30µin (0.76µm) Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	ACC43D1 G5 Specifications	
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 43 Number of Positions 86 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Manufacturer Part Number	ACC43DPGS
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row43Number of Positions86Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 43 Number of Positions 86 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 43 Number of Positions 86 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row43Number of Positions86Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Package	-
Gender Female Number of Positions/Bay/Row 43 Number of Positions 86 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Series	-
Number of Positions/Bay/Row43Number of Positions86Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Hairpin Bellows Color Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	43
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions	86
Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
Features Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 30μin (0.76μm) Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Number of Rows	2
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $30\mu in (0.76\mu m)$ Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125 " ($3.18mm$) DiaOperating Temperature -65 °C ~ 150 °C	Pitch	0.100" (2.54mm)
Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, $0.125''$ ($3.18mm$) Dia Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $30\mu in (0.76\mu m)$ Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, $0.125''$ ($3.18mm$) DiaOperating Temperature -65° C ~ 150° C	Mounting Type	Through Hole, Right Angle
Contact Finish Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Termination	Solder
Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Material	Beryllium Copper
Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Contact Finish	Gold
Color - Side Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature - 65 °C ~ 150 °C	Contact Finish Thickness	30μin (0.76μm)
Flange Feature Side Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature -65 °C ~ 150 °C	Contact Type	Hairpin Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	-
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors?

ACC43DPGS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ACC43DPGS Payment Methods



















ACC43DPGS Shipping Methods













If you have any question about ACC43DPGS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com