



ACC60DRMN Information

Heisener.com

Part Number ACC60DRMN

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 120POS .100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ACC60DRMN Specifications

| Manufacturer Part Number ACC60DRMN Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 60 Number of Positions 120 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Beryllium Copper Contact Finish Thickness 30µin (0.76µm) Contact Tips Thickness 30µin (0.76µm) Cotor - Flange Feature - Operating Temperature -65°C ~ 150°C | . | |
|---|-----------------------------|---|
| Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 60 Number of Positions 120 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Beryllium Copper Contact Finish Gold Contact Type Loop Bellows Color - Flange Feature - Operating Temperature -65°C ~ 150°C | Manufacturer Part Number | ACC60DRMN |
| Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 60 Number of Positions 120 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color - Flange Feature - Operating Temperature -65°C ~ 150°C | Manufacturer | Sullins Connector Solutions |
| Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row60Number of Positions120Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColor-Flange Feature-Operating Temperature-65°C ~ 150°C | Category | Connectors, Interconnects |
| Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 60 Number of Positions 120 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color - Flange Feature - Operating Temperature -65°C ~ 150°C | | Card Edge Connectors - Edgeboard Connectors |
| Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row60Number of Positions120Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange Feature-Operating Temperature-65°C ~ 150°C | Package | - |
| Gender Female Number of Positions/Bay/Row 60 Number of Positions 120 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color - Flange Feature - Operating Temperature -65°C ~ 150°C | Series | - |
| Number of Positions/Bay/Row 60 Number of Positions 120 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color - Flange Feature - Operating Temperature -65°C ~ 150°C | Card Type | Non Specified - Dual Edge |
| Number of Positions 120 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color - Flange Feature - Operating Temperature -65°C ~ 150°C | Gender | Female |
| Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange Feature-Operating Temperature-65°C ~ 150°C | Number of Positions/Bay/Row | 60 |
| Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange Feature-Operating Temperature-65°C ~ 150°C | Number of Positions | 120 |
| Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange Feature-Operating Temperature-65°C ~ 150°C | Card Thickness | 0.093" (2.36mm) |
| Features Mounting Type Through Hole Termination Wire Wrap Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color - Flange Feature Operating Temperature65°C ~ 150°C | Number of Rows | 2 |
| Mounting TypeThrough HoleTerminationWire WrapContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange Feature-Operating Temperature-65°C ~ 150°C | Pitch | 0.100" (2.54mm) |
| Termination Wire Wrap Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color - Flange Feature - Operating Temperature -65°C ~ 150°C | Features | - |
| Contact Material Contact Finish Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color Flange Feature Operating Temperature Beryllium Copper Gold | Mounting Type | Through Hole |
| Contact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange Feature-Operating Temperature-65°C ~ 150°C | Termination | Wire Wrap |
| Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Loop Bellows Color - Flange Feature - Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$ | Contact Material | Beryllium Copper |
| Contact Type Loop Bellows Color - Flange Feature - Operating Temperature -65°C ~ 150°C | Contact Finish | Gold |
| Color-Flange Feature-Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$ | Contact Finish Thickness | 30μin (0.76μm) |
| Flange Feature - Operating Temperature -65°C ~ 150°C | Contact Type | Loop Bellows |
| Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$ | Color | - |
| | Flange Feature | - |
| Report errors? | Operating Temperature | -65°C ~ 150°C |
| | | Report errors? |

ACC60DRMN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ACC60DRMN Payment Methods





















ACC60DRMN Shipping Methods













If you have any question about ACC60DRMN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com