



### **ACM36DSEF Information**

Heisener.com

Part Number ACM36DSEF

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 72POS 0.156

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **ACM36DSEF Specifications**

Manufacturer Part Number       ACM36DSEF         Manufacturer       Sullins Connector Solutions         Category       Connectors, Interconnects         Package       -         Series       -         Card Type       Non Specified - Dual Edge         Gender       Female         Number of Positions/Bay/Row       36         Number of Positions       72         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.156" (3.96mm)         Features       -         Mounting Type       Panel Mount         Termination       Solder Eyelet(s)         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Type       Full Bellows         Color       Green         Flange Feature       Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia         Operating Temperature       -65°C ~ 150°C	Menisoboli specifications	
Category Cand Edge Connectors - Edgeboard Connectors  Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 36 Number of Positions 72 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 150°C	Manufacturer Part Number	ACM36DSEF
Card Edge Connectors - Edgeboard Connectors  Package  Series  - Card Type  Non Specified - Dual Edge  Gender  Female  Number of Positions/Bay/Row  36  Number of Positions  72  Card Thickness  0.062" (1.57mm)  Number of Rows  2  Pitch  0.156" (3.96mm)  Features  Mounting Type  Panel Mount  Termination  Solder Eyelet(s)  Contact Material  Beryllium Copper  Contact Finish  Gold  Contact Type  Full Bellows  Contact Type  Full Bellows  Color  Green  Flange Feature  Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia  Operating Temperature  -65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 36 Number of Positions 72 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 150°C	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 36 Number of Positions 72 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors
Card Type Gender Female Number of Positions/Bay/Row 36 Number of Positions 72 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 150°C	Package	-
GenderFemaleNumber of Positions/Bay/Row36Number of Positions72Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Series	-
Number of Positions/Bay/Row       36         Number of Positions       72         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.156" (3.96mm)         Features       -         Mounting Type       Panel Mount         Termination       Solder Eyelet(s)         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       30μin (0.76μm)         Contact Type       Full Bellows         Color       Green         Flange Feature       Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia         Operating Temperature       -65°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions72Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	36
Number of Rows       2         Pitch       0.156" (3.96mm)         Features       -         Mounting Type       Panel Mount         Termination       Solder Eyelet(s)         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       30μin (0.76μm)         Contact Type       Full Bellows         Color       Green         Flange Feature       Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia         Operating Temperature       -65°C ~ 150°C	Number of Positions	72
Pitch       0.156" (3.96mm)         Features       -         Mounting Type       Panel Mount         Termination       Solder Eyelet(s)         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       30μin (0.76μm)         Contact Type       Full Bellows         Color       Green         Flange Feature       Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia         Operating Temperature       -65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
Features  Mounting Type Panel Mount  Termination Solder Eyelet(s)  Contact Material Beryllium Copper  Contact Finish Gold Contact Finish Thickness 30μin (0.76μm)  Contact Type Full Bellows  Color Green  Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia  Operating Temperature -65°C ~ 150°C	Number of Rows	2
Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $30\mu$ in $(0.76\mu$ m)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, $0.116$ " (2.95mm) DiaOperating Temperature $-65$ °C $\sim 150$ °C	Pitch	0.156" (3.96mm)
Termination Solder Eyelet(s)  Contact Material Beryllium Copper  Contact Finish Gold  Contact Finish Thickness 30 $\mu$ in (0.76 $\mu$ m)  Contact Type Full Bellows  Color Green  Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia  Operating Temperature -65°C ~ 150°C	Features	-
Contact Material Beryllium Copper  Contact Finish Gold  Contact Finish Thickness $30\mu$ in $(0.76\mu$ m)  Contact Type Full Bellows  Color Green  Flange Feature Top Mount Opening, Floating Bobbin, $0.116$ " (2.95mm) Dia  Operating Temperature $-65$ °C $\sim 150$ °C	Mounting Type	Panel Mount
Contact Finish Gold  Contact Finish Thickness $30\mu$ in $(0.76\mu m)$ Contact Type Full Bellows  Color Green  Flange Feature Top Mount Opening, Floating Bobbin, $0.116$ " $(2.95mm)$ Dia  Operating Temperature $-65^{\circ}$ C $\sim 150^{\circ}$ C	Termination	Solder Eyelet(s)
Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, $0.116''$ (2.95mm) Dia Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Material	Beryllium Copper
Contact Type  Full Bellows  Color  Green  Flange Feature  Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia  Operating Temperature  -65°C ~ 150°C	Contact Finish	Gold
Color Green  Flange Feature Top Mount Opening, Floating Bobbin, $0.116$ " (2.95mm) Dia  Operating Temperature $-65$ °C $\sim 150$ °C	Contact Finish Thickness	30μin (0.76μm)
Flange Feature Top Mount Opening, Floating Bobbin, $0.116$ " (2.95mm) Dia Operating Temperature $-65$ °C $\sim 150$ °C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Green
	Flange Feature	Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia
	Operating Temperature	-65°C ~ 150°C
Report errors'		Report errors?

### **ACM36DSEF Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ACM36DSEF Payment Methods**



















## **ACM36DSEF Shipping Methods**













If you have any question about ACM36DSEF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com