

ACR05D332JGS

Request a Quote

ACR05D332JGS Information

Contraction of the second seco	Part Number	ACR05D332JGS
	Manufacturer	KEMET
	Category	Capacitors Ceramic Capacitors
	Description	CAP CER 3300PF 100V NP0 RADIAL
	Package	Radial
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ACR05D332JGS Specifications

Manufacturer Part Number ACR05D332JGS Manufacturer KEMET Catagory Capacitors Caranic Capacitors Ceranic Capacitors Package Radial Series ACR Capacitance 300pF Tolerance ±5% Voltage - Rated 000 V Operating Temperature 050°C ^ 200°C Pactures General Purpose Applications General Purpose Applications General Purpose Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200°C 1.5.08mm x 2.54mm) Height Seated (Max) 0.200°C 1.5.08mm x 2.54mm) Package / Case Radial Size / Dimension General Purpose Height Seated (Max) 0.200°C 1.5.08mm x 2.54mm) Height Seated (Max) 0.200°C 1.5.08mm x 2.54mm) Lead Spacing 0.200°C 1.5.08mm)		
CategoryCapacitorsPackageRadialSeriesACRCapacitance3300pFCapacitance±5%Voltage - Rated100VTomperature CoefficientCOG, NPOOperating Temperature-55°C ~ 200°CFaturesHigh TemperatureArging-Arging Sanger-Applications-FaturesCong NPOFatures-Aunting Type-Package / Case-Size / Dimension-Hight Seated (Max)-Hight Seated (Max)-Hight-Seated (Max)-Fatures (Max)-Applications-Size / Dimension-Size / Dimension-Hight-Seated (Max)-Hight-Seated (Max)-Lead Spacing-Lead Spacing-Lead Spacing-Lead StyleSingih	Manufacturer Part Number	ACR05D332JGS
Indext of the section of the sectio	Manufacturer	KEMET
PackageRadialSeriesACRCapacitance3300pFTolerance5%Voltage - Rated100VTemperature CoefficientCOG, NP0Operating Temperature55°C ~ 200°CFeaturesHigh TemperatureRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200°L x 0.100°W (5.08mm x 2.54mm)Height - Seated (Max)-Hickness (Max)-Lead Spacing0.200°L (5.08mm)Lead StyleStraight	Category	Capacitors
Constraint ACR Capacitance 3300pF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 200°C Features High Temperature Ratings - Applications General Purpose Failure Rate - Nouthing Type Through Hole Size / Dimension 0.200" (L x 0.100" W (5.08mm x 2.54mm)) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Straight		Ceramic Capacitors
Capacitance3300pFTolerance±5%Voltage - Rated100VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 200°CFeaturesHigh TemperatureRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HoleSize / Dimension0.200° L x 0.100° W (5.08mm x 2.54mm)Hight - Seated (Max)-Thickness (Max)-Lead Spacing0.200° (5.08mm)Lead StyleStraight	Package	Radial
Tolerance±5%Voltage - Rated100VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 200°CFeaturesHigh TemperatureRatings-ApplicationsGeneral PurposeFaiture Rate-Mounting TypeRadialPackage / CaseRadialSize / Dimension0200° L x 0.100° W (5.08mm x 2.54mm)High Seated (Max)-High Seated (Max)-Lead Spaine0200° (5.08mm)Lead StyleSize (Max)Size / Dimension-States (Max)-States (Max)-S	Series	ACR
Voltage - RatedIOOVTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 200°CFeaturesHigh TemperatureRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.100" W (5.08mm x 2.54mm)Height - Seated (Max)-Thickness (Max)0.200" (5.08mm)Lead SpacingStraight	Capacitance	3300pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 200°CFeaturesHigh TemperatureRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.100° W (5.08mm x 2.54mm)Hight - Seated (Max)-Thickness (Max)0.200° (5.08mm)Lead SpacingStraight	Tolerance	±5%
Operating Temperature-55°C ~ 200°CFeaturesHigh TemperatureRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.100" W (5.08mm x 2.54mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Voltage - Rated	100V
FeaturesHigh TemperatureRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.100" W (5.08mm x 2.54mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.100" W (5.08mm x 2.54mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Operating Temperature	-55°C ~ 200°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.100" W (5.08mm x 2.54mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)0.200" (5.08mm)Lead Spacing0.200" (5.08mm)Lead StyleStraight	Features	High Temperature
Failure Rate-Founting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.100" W (5.08mm x 2.54mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Ratings	-
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.100" W (5.08mm x 2.54mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Applications	General Purpose
Package / CaseRadialSize / Dimension0.200" L x 0.100" W (5.08mm x 2.54mm)Height - Seated (Max)0.200" (5.08mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Failure Rate	-
Size / Dimension 0.200" L x 0.100" W (5.08mm x 2.54mm) Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max) 0.200" (5.08mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Straight	Package / Case	Radial
Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Size / Dimension	0.200" L x 0.100" W (5.08mm x 2.54mm)
Lead Spacing0.200" (5.08mm)Lead StyleStraight	Height - Seated (Max)	0.200" (5.08mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.200" (5.08mm)
Report errors?	Lead Style	Straight
		Report errors?

ACR05D332JGS Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ACR05D332JGS Payment Methods





If you have any question about ACR05D332JGS, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com